OCD-ARTESIA UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEN Month - Year NM070603 SUNDRY NOTICES AND REPORT MAR 2 1 2007 6. If Indian Allottee or Tribe Name Do not use this form for proposals to dril enter an OCD - ARTESIA, NIM abandoned well. Use Form 3160 - 3 (APD) to oposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE- Other instructions on reverse side. 35256 1. Type of Well X Oil Well Gas Well Other 8. Well Name and No. Shearn Becky Federal #1 2 Name of Operator C & D Management Company 231382 API Well No. 30-015-3444#0 la Address 513 Don Lyle Road 3b. Phone No. (include area code) 270-565-4629 10. Field and Pool, or Exploratory Area Empire Yates 7 Rivers Edmonton, KY 42129 4. Location of Well (Footoge, Sec., T., R., M., or Survey Description) 11. County or Parish, State 660' FNL & 1650' FEL (Unit B, NWNE) Section 14-T17S-R27E 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Acidize Deepen Water Shut-Off Production (Start/Resume) Notice of Intent Alter Casing Well Integrity Fracture Treat Reclamation Casing Repair Other New Construction Recomplete Subsequent Report Plug and Abandon Change Plans Temporarily Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markets and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) We are proposing to plug and abandon the above well by placing a plug at bottom of hole and 25 sacks Class C cement then placing a plug at top of 25 sacks Class C cement. Total depth of well is 750 feet. This well is under bond #NMB0002455

14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Darla Jeffries  Signature	Title	President			
- Auria Frauco 1	Dete				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by		Title	Dete		APPROVED
Conditions of approval, if any, are attached. Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject lea which would entitle the applicant to conduct operations thereon.	se ,	Office			MAD 1 0 2007
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.					
(Instructions on page 2)				P	FREDERICK WRIGHT ETROLEUM ENGINEER

SEE ATTACHED FOR CONDITIONS OF APPROVAL

Accepted for record NMOCD

## SUNDRY NOTICE SPECIAL STIPULATIONS

- 1. Approval is granted to P/A this well with the following modifications to the procedure:
- 2. Add 25 sack plug @ 350 feet which can be combined with the surface plug.
- 3. Set abandonment marker.
- \* All plugs, including the surface plug, should leave at least 25 sacks of cement inside the casing and be at least 100 feet, plus an additional 10% for each 1000 feet of depth.

Plugging procedures must conform to 43 CFR 3162.6.d and Onshore Order No. 2.111.G or NMOCD orders if they are more stringent.

All of the work approved here must be completed within 90 days

Engineering can be reached at 505-706-2779 for any variances that might be necessary.

F Wright 3/19/07

Accepted for record NMOCD