District I 1625 N. Francis Dr., Hobbs, NM 88246 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Huzzos Rood, Aztec, NM 97410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87305

## State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

ling and production facilities, submit to ate NMOCD District Office. it to Santa Fe

Form C-144 June 1, 2004

11

rys,

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No.

| Type of action: Registration of a pit  | orbolow-gande bank [] Closure of a pit or bolow-gan  | le tank 🗵  |
|--|--|--|
| Membrurne Dil Co. Topon  | (565) 373-5905 omail address:  | 1. A   |
| P.O. Box 5270 Hobs NM  | 18241  |  |
| City or well super, TAMANO 15 Fed. # 3 APE   | 30-015-34442 WE - COMO C   | Sec 15 TIPS R31E   |
| my: Eddy Lating  | N32.45' 13.2" Land W/03"   | 5/35/ NAD: 1927 1983   |
| chec Owner: Pedicial   State   Private   Indian  | 7,000  |  |
|  | Balon-grade tank   |  |
| k<br>1955 Drilling 🖒 Production 🗌 Disposal 🗍   | Volume: Nel Type of fluid:   |  |
| Workower Bracegency  | Construction pasterial:  |  |
| nel 🖄 United 🖸   | Double-walled, with lask detection? Yes- E Knot, explain vely not.   |  |
| ner type: Synthetic A Thickness 12 mil Clay  |  |  |
| Volume bil   |  |  |
|  | Loss than 50 feet  | (26 points)  |
| opts to ground water (vertical distance from bottom of pit to someonal   | 50 fact or more, but less than 100 feet  | (10 points)  |
| gh water elevation of ground water.)   | 100 Seat or more 400'  | (Opoints)  |
|  | Yes  |  |
| Felthend protection area: (Less than 200 feet from a private domestic  | No No  | (20 points)  |
| ster source, or lose than 1600 feet from all other unter sources.)   | 4  | ( o puess)   |
| intance to surface water: (horizontal distance to all wetlamin, playes,  | Loss than 200 first  | (20 points)  |
| rigation canals, dischos, and percential and aphonesis watercourses.)  | 290 fact or mero, but less than 1000 feet  | (10 points)  |
|  | 1000 fact or marc  | ( Opeists)   |
|  | Ranking Score (Total Points)   | 0  |
| sociation start date and end date. (4) Groundwater encountered: No X<br>Attach soil enumbs results and a fingerin of semigle legislams and encountered.<br>Additional Comments: Keter to AHA CLE                     | •  |  |
|  |  |  |
| Date: 5/24 07 Printed Name/Title 1854 L. W. SXN Fill Ag. Your confilication and NMOCD approval of this application cleanure des otherwise cadenger public health or the cavinements. Her date it salice regulations. | ent some hydring the state of t | the above described pit or below-grade tand attive OCD approved plan |
| Approval:  | - Alla Kan   |  |
| Printed Name/Title   | Signature JULIU Service  | Date: 6/4/07   |
| sit elecure pit ar   | les are to be obtained from ea and analysis submitted to   |  |

NMOCD prior to back-filling

P.O. Box 310 Hobbs, NM 88241-0310

New Mexic Environmental Services

Hobbs. New Mexico 505.392.8584 Cell 505.631.2442 Fax 505.392.3085

**Hobbs, New Mexico** 

Reserve Pit Remediation

## **SURFACE PIT CLOSURE PLAN**

## PIT PARAMETERS

COMPANY: Mewbourne Oil Co. WELL SITE: Tamano 15 Fed #3

LEGAL DESCRIPTION: Unit C Sec 15 T18s R31e, 400

FNL 1900 FWL, Eddy co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 150' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 1800 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.