

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD-ARTESIA

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Fairway Resources Operating, LLC

3a. Address

538 Silicon Drive, Suite 101, Southlake, TX 76092

3b. Phone No. (include area code)

817/416-1946

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2,080 FNL & 560' FEL Section 35-T17S-R27E

5. Lease Serial No.

NM LC050158

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

NM 109695X

8. Well Name and No

South Red Lake II Unit 14

9. API Well No.

30-015-05596

10. Field and Pool, or Exploratory Area

Redlake, QN, GB, SA

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

5 1/2" 14# J-55 casing set at 1,598', cmt circulated to surface

TD 1,621'

3/2007 CIBP set at 1,525', MIT failed.

1. TIH with tubing and spot 50' cmt plug on CIBP at 1,525'
2. Tag plug, circulate abandonment mud.
3. Spot 100' cmt plug at 700' with tubing.
4. Tag plug at 700' and circulate abandonment mud.
5. Spot 60' cmt plug at surface and install dry hole maker
6. Clean and remediate location

ACCEPTED FOR RECORD

JUN 26 2007

Gerry Guye, Deputy Field Inspector
NMOCD-District II ARTESIA

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Kenneth Pearce

Title Engineer

Signature

Date

06/13/2007


THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon

Title

Office



Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

(Instructions on page 2)

SUNDRY NOTICE SPECIAL STIPULATIONS

1. Approval is granted to P/A this well with the following modifications to the procedure:
2. The plug proposed for 700' should be a minimum of 25 sacks.
3. The surface plug should be a minimum of 25 sacks and 100'

*** All plugs, including the surface plug, should leave at least 25 sacks of cement inside the casing and be at least 100 feet, plus an additional 10% for each 1000 feet of depth.**

Plugging procedures must conform to 43 CFR 3162.6.d and Onshore Order No. 2.III.G or NMOCD orders if they are more stringent.

All of the work approved here must be completed within 90 days

Engineering can be reached at 505-706-2779 for any variances .

F Wright 6/20/07

Fairway Resources Operating, LLC
South Red Lake II Grayburg Unit #14

API 30-015-05596
2080' FNL and 560' FEL
Sec.35, T17S, R27E
Eddy County, NM

Spud 9-13-54
Elev. 3614'

