Submit 3 Copies to Appropriate

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89 District Office DISTRICT I P.O. Box 1980, Hobbs NM 88240 OIL CONSERVATION DIVISION WELL API NO. 2040 South Pacheco 30-015-32749 Santa Fe, New Mexicol 8 <u>DISTRICT II</u> 811 South First, Artesia, NM 88210 5. Indicate Type of Lease STATE 🛛 FEE **DISTRICT III** 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd, Aztec, NM 87410 B-2613 SUNDRY NOTICES AND REPORTS **101** WE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DESEEN OR PIX DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMON 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS). 1. Type Of Well: OIL GAS П Safari 36 State Com OTHER WELL 8. Well No. 2. Name of Operator Mack Energy Corporation 9. Pool name or Wildcat 3. Address of Operator P.O. Box 960, Artesia, NM 88211-0960 Cedar Lake Morrow, East 4. Well Location South Unit Letter Feet From The _ Line and Feet From The Line NMPM Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3848' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT TEMPORARILY ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** Spud and Cement Casings OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 06/22/2003 Spud 17 1/2" hole 12:00 AM. 06/24/2003 TD 17 1/2 hole @ 821', RIH w/13 3/8" 54.5# J-55 ST&C set @ 821', Cemented w/450 sx Class C, 6# salt, 1/4# CF, tail in w/250 sx Class C, 2% CC, plug down 6:45 PM, circ 143 sx. WOC 18 hours tested casing to 1800# for 30 minutes, held OK. 07/05/2003 TD 11" hole @ 5006'. 07/06/2003 RIH w/8 5/8" casing 112 joints set @ 5006', Cemented w/1200 sx 35-65-6, 3# salt, 1/4# CF, tail in w/850 sx 50-50-2, 5% KCL, 5# gil, 1% FL25, .2% FL52, .3% SMS, circ 275 sx. WOC 12 hours tested casing to 600# for 20 minutes, held OK. 08/12/2003 TD 7 7/8" hole @ 12720'. 08/20/2003 RIH w/5 1/2" casing 17# P-110 and N-80 LT&C 294 joints set @ 12,720', Cemented 1st stage w/675 sx Class C Poz, .7% FL52, .7% FL25, 1% BA10, 2% KCL, 5# LCM-1, 2nd stage 800 sx Class C Poz, .6% FL25, .6% FL52, 1% BA10, 3% KCL, WOC 12 hours tested casing to 600# for 20 minutes, held OK. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 9/25/2003 Production Clerk Jerry W. Sherrell

Partict Supervisor

APPROVED BY-

lim W. Gum