## Form 3160-5 (April 2004)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0135

SUN	<b>IDRY</b>	NOTICES	AND	REPORTS	ON.	WELL	.S
D.	not us	a this form fo	r nron	osals to drill o	r re e	nter an	

Expires March 31, 2007

SUNDRY N	5. Lease Senal No. NM-34647 6 If Indian, Allottee or Tribe Name							
wabandoned we								
SUBMIT IN TRIPL	7. If Unit or CA/Agreement, Name and/or No.							
1 Type of Well Oil Well Ga	as Well X Other P&A			8 Well Name and	No			
2. Name of Operator	<del></del>	Charolette McKay Federal SWD #1						
Yates Petroleum Corporatio		9 API Well No						
3a Address		No (include area code)	)	30-015-23095				
105 S. 4th Str., Artesia, NM		505-748-1471		1	, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., N	., OR Survey Description)				SWD-Devonian			
			11 County or Parish, State					
1980'FNL & 660'FEL of Section	VACETOR DE	Eddy County, New Mexico						
12. CHECK APPROF	PRIATE BOX(ES) TO INDICA			PORT, OR OT	THER DATA			
TYPE OF SUBMISSION		ТҮРЕ С	F ACTION					
	Acıdıze	Deepen	Production (	Start/Resume)	Water Shut-Off			
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	,	Well Integrity			
		1	芦					
X Subsequent Report	Casing Repair	New Construction Recomplete			Other			
	Change Plans X	Plug and Abandon	lug and Abandon Tempotanly Abandon					
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dispo	sal				
following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  1/7/02 Set 5-1/2" CIBP at 9640'. Dump bailed 35' cement on top.  1/8/02 Circulated hole w/mud laden fluid. Spot 25 sx Class "C" neat cement at 9164' to 8917'. Spot 25 sx Class "C" neat cement at 8846'. WOC. Tagged plug at 8580'.  1/9/02 Spot 25 sx Class "C" neat cement at 6173' to 5926'.  1/10/02 Cut and pull 5-1/2" casing at 3669'.  1/11/02 Spot 40 sx Class "C" neat cement at 4032' (stub plug). WOC. Tagged at 3910'.  1/14/02 Spot 40 sx Class "C" neat cement at 3648' to 3492'. Spot 40 sx Class "C" neat cement at 2304' to 2148'. Spot 50 sx Class "C" neat cement at 2048'. WOC. Tagged at 1876'.  1/15/02 Spot 50 sx Class "C" neat cement at 420'. WOC 4 hrs. Tagged at 225'. Circulated 25 sx Class "C" neat cement at 60' to surface. Installed dry hole marker.  NOTE: This was previously submitted on Form C-103 (state form - attached), re-submitting on Form 3160-5 as per Carlsbad BLM								
14 I hereby certify that the foregoing is tru	e and correct							
Name (Printed/Typed) Tina H	lwerta	Title Regula	atory Complia	ar <b>AESEDET</b> III	DFOR RECORD			
Signature (Juna)	herte	Date July 18						
	THIS SPACE FOR FED	ERAL OR STATE O	FFICE USE	JUL	2.3.2007			
Approved by		Title		Gerry Guye De	puty Field Inspector			
Conditions of approval, if any, are attache certily that the applicant holds legal or ed which would entitle the applicant to conduct	quitable title to those rights in the subject	rant or		NMOCD-Dist	trict II ARTESIA			

Title 18 U.S C Section 1001 and Title 43 U.S C Section 1212, make it a crime for any person knowingly and willbully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction