Form 3160-5 (September 2001)

## New Mexico Oil Conservation District I 1623 N. French Dri UNITED STATES DEPARTMENT OF THE INTERIOR

Hobbs, NM 88240

FORM APPROVED OMB No 1004-0135

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.		Expues January 31, 2004
		5 Lease Serial No.
		NM-28179 6 If Indian, Allottee or Tribe Name
		7 If Unit or CA/Agreement, Name and/or No
SUBMIT IN TRIPLICATE - Other inst	ructions on reverse side	- HOME OF CAPAGREEMENT, Name and/or No
1. Type of Well  A Oil Well  Gas Well  Other	II 4	8 Well Name and No
	OCD-ARTESIA	
2 Name of Operator Yates Drilling Company	OCD-ARTESIA	Fredia Federal #1
3a. Address	3b Phone No. (include area code)	30-005-20978
105 S. 4th Str., Artesia, NM 88210	505-748-8663	10 Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec ,T ,R ,M., OR Survey Description)		Caprock Queen
		11 County or Parish, State
1650' FNL & 1700' FEL Se		Chaves Co., NM
12 CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF NOTICE, I	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Acidize	Deepen Production	n (Start/Resume) Water Shut-Off
Notice of Intent Alter Casing	Fracture Treat Reclamate	on Well Integrity
Casing Repair	New Construction Recomple	te Other
Subsequent Report Change Plans		ıly Abandon
Final Abandonment Notice Convert to Injection		
Describe Proposed of Completed Operation (clearly state all pertinent details,	L	
Attach the Bond under which the work will be performed or provide the Bond following completion of the involved operations. If the operation results in a testing has been completed. Final Abandonment Notices shall be filed only determined that the site is ready for final inspection.)  6/12/07 Notified BLM, Gary Gorley.  6/13/07 Set 5 1/2" CIBP @ 2,960'.  6/14/07 Circulated 9.5# MLF. Spotted 25 sxs. Could not circulate. Spotted 25 sxs. Could not circulate. Spotted 25 sxs. Could not circulate. Spotted 25 sxs. Geology Perforated at 1,000' and squeezed perforated at 459'. Set packer at 250' Gurley, BLM.  6/18/07 Squeezed 100 sxs cement w/ 2% CaC Hogwood, BLM. Pumped 20 sxs cement Removed wellhead and anchors. Installation.	cement 2,960'-2,780'. Perforated a sement at 1,650'- 1,404' per instruction from the 25 sxs cement with 2% CaC and squeezed with 100 sxs cement Cl. Tagged cement at 359'. Perforated fent down 5 1/2" csg and circulated to	orm 3160-4 shall be filed once ompleted, and the operator has at 1432'. Set packer at 1,342'. ons from Gerry Gurley, BLM. It with 600 psi @ 3/bbl/min. It per instructions from Gerry ted at 60', per J.R. to surface.
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)	JUL 2 7 2007	
Karen J. Leishman	Title Operations Tech	GARY GOURLEY PETRO! FUM ENGINEER
Gerry Guye, Deputy Field Inspector  NMOCD-District II A BURESTOR		
Signature This space for Federal Or State Office USE		
		D.:
Approved by  Conditions of approval, if any, are attached Approval of this notice do	Title	Date
certify that the applicant holds legal or equitable title to those rights		