Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I Ener	rgy, Minerals and Natural Resources	• May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II 1301 W Grand Ave., Artesia, NM 88210 OII	L CONSERVATION DIVISION	30-015-35679
District III	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		B-7762
SUNDRY NOTICES AND		7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DR DIFFERENT RESERVOIR. USE "APPLICATION FOR		
PROPOSALS.) 1. Type of Well: Oil Well Gas Well	☑ Other	BEAR DRAW STATE COM 8. Well Number 1
2. Name of Operator	DEC 17 2007	9. OGRID Number 015363
MURCHISON OIL &	& GAS, INC. OCD_ADTESIA	7. GORD Hamor Grass
3. Address of Operator	UULIARI ESIA	10. Pool name or Wildcat
	BLVD., PLANO, TX. 75093-4698	GRAYBURG, MORROW
4. Well Location		
Unit Letter <u>B</u> : <u>660</u>	feet from theN line and _	$\underline{1980} \qquad \text{feet from the} \qquad \underline{\text{E}} \qquad \text{line}$
	1 0	PM County EDDY
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3640 GR		
Pit or Below-grade Tank Application or Closure		
Pit typeDepth to Groundwater	Distance from nearest fresh water welll	Distance from nearest surface water
Pit Liner Thickness: mil Below-	-Grade Tank: Volumebbls;	Construction Material
12. Check Appropria	ate Box to Indicate Nature of Notic	e. Report or Other Data
NOTICE OF INTENTIC		BSEQUENT REPORT OF:
	ND ABANDON REMEDIAL WO	
		RILLING OPNS. P AND A
	'LE COMPL 🔲 CASING/CEME	INT IOR I I
PULL OR ALTER CASING MULTIP	0,101110,021111	141 30B
_		_
OTHER:	☐ OTHER:	DRILLING/CEMENT
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE	OTHER:	_
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion.	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions:	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion.	OTHER:	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion.	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: ,780'. Ran 5-1/2" production casing as fo	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10,	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: ,780'. Ran 5-1/2" production casing as fo	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as fo e 1' 7 P-110 LT&C 43' 2'	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of th	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of th	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of th	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoet 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of th	DRILLING/CEMENT
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with	OTHER: ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 5780'. Ran 5-1/2" production casing as for the state of	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion llows: KS 50/50/10 "C" cement + .8% FL-52A + 5#
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE for recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield 2.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion allows: AS 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7%
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield 2.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion allows: AS 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% als. H2O. Bump plug with 2156#, floats held.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion allows: AS 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% als. H2O. Bump plug with 2156#, floats held.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion clows: (S 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% ols. H2O. Bump plug with 2156#, floats held. up "C" section, test to 5000#. Jet and clean pits.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion clows: (S 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% ols. H2O. Bump plug with 2156#, floats held. up "C" section, test to 5000#. Jet and clean pits.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for the state of the state	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion clows: (S 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% ols. H2O. Bump plug with 2156#, floats held. up "C" section, test to 5000#. Jet and clean pits.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007.	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for 1' 7-110 LT&C 43' 2' 7-110 LT&C 6424' N-80 LT&C 4316' 10786' 12 bbls. Mudclear spacer ahead + 1375 S. 3, slurry 563 bbls. Tail with 450 SXS 15. 1.6, slurry 128 bbls. Displace with 250 bl BOP, set slips and cut off casing. Nipple True and complete to the best of my knowled the state of the set of my knowledge of the set of	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion clows: (S 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% ols. H2O. Bump plug with 2156#, floats held. up "C" section, test to 5000#. Jet and clean pits.
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoe 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007. I hereby certify that the information above is tregrade tank has been/will be constructed or closed according to the start of t	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for 1' 7 P-110 LT&C 43' 2' 7 P-110 LT&C 6424' N-80 LT&C 4316' 10786' 12 bbls. Mudclear spacer ahead + 1375 S. 3, slurry 563 bbls. Tail with 450 SXS 15. 1.6, slurry 128 bbls. Displace with 250 bl BOP, set slips and cut off casing. Nipple Tue and complete to the best of my knowledging to NMOCD guidelines □, a general permit	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion completion discrete diagram of proposed completion discrete discrete diagram of proposed completion discrete disc
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoot 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007. I hereby certify that the information above is treated tank has been/will be constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to	ations. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 780'. Ran 5-1/2" production casing as for 1' 7 P-110 LT&C 43' 2' 7 P-110 LT&C 6424' N-80 LT&C 4316' 10786' 12 bbls. Mudclear spacer ahead + 1375 S. 3, slurry 563 bbls. Tail with 450 SXS 15. 1.6, slurry 128 bbls. Displace with 250 bl BOP, set slips and cut off casing. Nipple Tue and complete to the best of my knowledging to NMOCD guidelines □, a general permit	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion completion discrete diagram of proposed completion discrete discrete diagram of proposed completion discrete disc
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoot 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007. I hereby certify that the information above is treated tank has been/will be constructed or closed according to the state Use Only Type or print name MICHAEL S. DAUGHER For State Use Only	TITLE PRESIDEN Actions. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 1,780'. Ran 5-1/2" production casing as for the state of the pertinent details, RULE 1103. For Multiple Completions: 1,780'. Ran 5-1/2" production casing as for the state of t	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion allows: AS 50/50/10 "C" cement + .8% FL-52A + 5# 61/11 "C" CSE-2 cement + .7% FL-52A + .7% als. H2O. Bump plug with 2156#, floats held. ap "C" section, test to 5000#. Jet and clean pits. adge and belief. I further certify that any pit or below— are or an (attached) alternative OCD-approved plan allowed. TOPERATIONS DATE 11/3/07 ty@jdmii.com Telephone No. (972) 931-0700
OTHER: 13. Describe proposed or completed opera of starting any proposed work). SEE or recompletion. Drilled a 8-1/2" hole to a depth of 10, 1 DV Float Shoot 1 jt. 5-1/2" 17#/FT 1 Float Collar 153 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT 100 jts. 5-1/2" 17#/FT Set casing @ 10,779'. Cement with LCM-1 + 1/8# C/F, wt. 11.8, yield 2. FL-25 + .5% BA-10, wt. 13.2, yield Circulated 36 SXS to pit. Rig down Rig released 9:00 AM 10/6/2007. I hereby certify that the information above is treated tank has been/will be constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to the start of the constructed or closed according to	TITLE PRESIDEN Actions. (Clearly state all pertinent details, RULE 1103. For Multiple Completions: 1,780'. Ran 5-1/2" production casing as for the state of the pertinent details, RULE 1103. For Multiple Completions: 1,780'. Ran 5-1/2" production casing as for the state of t	DRILLING/CEMENT and give pertinent dates, including estimated date Attach wellbore diagram of proposed completion completion discrete diagram of proposed completion discrete discrete diagram of proposed completion discrete disc