<u>District I</u> 1625 N. French Dr , Hobbs, NM 88240 District II District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144 June 1, 2004

FEB 29 2008

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes M No

office

Type of action Registration of a pit of	or below-grade tank \(\subseteq \text{Closure of a pit or below-grade} \)	tank D OCD-ARTESIA
500°D		
Operator <u>EOGRResources</u> , Inc. <u>Telephon</u>	e·e-mail address:	
Address: PO BOX 2267, MIDLAND TX 79702 Facility or well name Salmon B32 St #1H API # 30-0(5-35862 U/L or Qtr/Qtr SW/4 Sec 32 T18S R23E		
	1880 ' FSL Longitude <u>660</u>	' FWL NAD 1927 ☐ 1983 ☐
Surface Owner: Federal State Private Indian		
<u>Pit</u>	Below-grade tank	
Type Drilling 🖾 Production 🗌 Disposal 🗍	Volumebbl Type of fluid	
Workover ☐ Emergency ☐	Construction material	
Lined M Unlined	Double-walled, with leak detection? Yes If not, explain why not	
Liner type: Synthetic [X] Thickness 12 mil Clay [
Pit Volume 16, 600 bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
, ,	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	Opoints)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	0 points)
water source, or less than 1000 feet from all other water sources.)		() ppinus)
Distance to surface water. (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	i i	(10 points)
inigation canais, diteries, and perchinar and ephonician watercourses.	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location (check the onsite box if		
,		
your are burying in place) onsite of offsite of lf offsite, name of facility (3) Attach a general description of remedial action taken including		
remediation start date and end date (4) Groundwater encountered No 💹 Yes 🔲 If yes, show depth below ground surfaceft and attach sample results		
(5) Attach soil sample results and a diagram of sample locations and excavations		
Additional Comments RECLAIM DRILLING PIT PER OCD REGULATIONS: DIG DEEP BURIAL HOLE, LINE		
WITH 12-MIL PLASTIC, MIX ALL CONTENTS IN PIT TO STIFFEN AND PLACE IN ENCAPSU-		
LATION TRENCH; CAP WITH 20-MIL, COVER WITH 3' OR MORE TOP SOIL OR LIKE MATERIAL.		
PULL SOIL SAMPLES FROM BOTTOM OF PIT; IF SAMPLES PASS, FILL IN OLD DRILLING PIT.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank		
has been/will be constructed or closed according to NMOCD guidelines 🗷, a general permit 🗌, or an (attached) alternative OCD-approved plan 🗍.		
Date: 2/19/08 MORGAN TOOLS CO., LLC		
Printed Name/Title Stephen Wilson, Foreman Signature Stephen Wilson		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval:	//	
Printed Name/Title	Signature Signed By Mily Bene	Date FEB 2 9 2008
		- LVVV

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling.

If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench.