<u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410		nservation Division	For drilling and production facilities, submit t appropriate NMOCD District Office.
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		outh St. Francis Dr. a Fe, NM 87505	For downstream facilities, submit to Santa Fe office
		Tank Registration or	
		overed by a "general plan"? Ye	
Type of action: Res	istration of a pit or be	low-grade tank Closure of a pit of	below-grade tank & OCD-ARTESIA-
operator (imarex (nerge Cool C	-longereichone:	505-628-3447 o-mail add	ress: dor Seyrogers @ Gol, Com
	artsbad in		
Facility or well name: Clen wood 28 32	2 #2 API #: 30.	-015-36140 U/LorQin	$\operatorname{Qtr}_{H} \xrightarrow{A} \operatorname{Scc}_{28} \operatorname{T}_{165} \operatorname{R}_{29} \operatorname{E}_{10}$
County: Cddy Co		-53'-53. 13"No Longitud	e 04°-05'-14,46 NAD: 1927 □ 1983 □
Surface Owner: Federal X State Private Indian			<i>i</i>
Pit Type: Drilling Production Disposel Workover Emergency		elow-grade tank olume: bbl Type of fluig:	10
		construction material:	
Lined D Unlined		Double-walled, with leak detection? Yes I If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay	ם _		-
Pit Volume 500 bbl			
Depth to ground water (vertical distance from bottom of	pit to seasonal	ess than 50 feet	(20 points)
high water elevation of ground water.) 125'	- 5	0 feet or more, but less than 100 feet	(10 points)
103 6	293 1	00 feet or more	(Opoints)
Wellhead protection area: (Less than 200 feet from a pri	ivate domestic	(cs	(20 points)
water source, or less than 1000 feet from all other water	sources.)		(Opoints)
Distance to surface water: (horizontal distance to all we		ess than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral w	2	00 feet or more, but less than 1000 fee	
		000 feet or more	(Opoints)
	F	tanking Score (Total Points)	-0-
If this is a pit closure: (1) Attach a diagram of the facilit	y showing the pit's rel	lationship to other equipment and tank	a. (2) Indicate disposal location: (check the onsite box if
your are burying in place) onsite 対 offsite 🗖 If offsite,	name of facility	(3) Attach	a general description of remedial action taken including
remediation start date and end date. (4) Groundwater enco	ountered: No 🕅 Yes	If yes, show depth below ground s	urfaceft. and attach sample results.
(5) Attach soil sample results and a diagram of sample loc	ations and excavation	8.	
Additional Comments:	<u> </u>	A	
See att	algod	workplan	
		V	
: 			
I hereby certify that the information above is true and co	mplete to the best of r	ny knowledge and belief. I further of	rtify that the above-described pit or below-grade tan
has been/will be constructed or closed according to N	MOCD guidelines []	A, a general permit [], or an (attach	ed) alternative OCD-approved plan [].
Date:	Dim.		
Printed Name/Title	- Sult	Signature TV	
Your certification and NMOCD approval of this applica otherwise endanger public health or the environment. N	tion/clouvre does not a	elieve the operator of liability should (he contents of the pit or tank contaminate ground water of ance with any other federal, state, or local laws and/or
regulations.	VVVV		
		A	· · · · · · · · · · · · · · · · · · ·
Approval:		Signed By Mile	Benny JUN 0 6 2008
Printed Name/Title		Signature	Date:

N

to back-filling. F

ŕ,



PHOENIX ENVIRONMENTAL LLC

P.O. Box 1856

2113 French Dr.

Hobbs, NM 88241-1856

Office 505-391-9685

Fax 505-391-9687

June 2, 2008

Cimarex Energy Co. 207 S. Mesa Carlsbad, New Mexico 88220

Attn: Mr. Dorsey Rogers Drilling Superintendent

RE: Work Plan and Cost to Clean Up the Glenwood 28 Fed # 2 Drilling Pit Located in UL A Sec 28, T16S and R29E of Eddy County, New Mexico

Dear Mr. Rogers:

Phoenix Environmental, LLC (Phoenix) would like to take this time to thank you and Cemarex Energy, for the opportunity to provide our professional services. Please find attached our work plan for the above listed site.

If you have any questions and/or need more data in regards to projects please call at any time. My cell phone is 575-631-8314.

Sincerely,

Allen Hodge, REM VP Operations Phoenix Environmental LLC



Summary/Overview

The Glenwood Fed 28 # 2 Drilling Pit site should be completed and remediated in accordance with the standards of the NMOCD. It is our understanding that any potential contamination from the site was a result of activities associated with the drilling and production of oil and gas.

The potential contaminates of concern are mid to high-level concentrations of drilling mud and cuttings that were left after drilling operations were completed.

The lands primary use is domestic pasture for ranching and the production of oil and gas.

The ground water depth data available for this area showed the depth to ground water to be in the 125' range BGS.

Pursuant to the standards of the NMOCD, the clean up level for this site will be at <5,000ppm of TPH, <50ppm for BTEX and Chlorides less than <250ppm.

The following scope of work was based on data from our site visit and the requirements of the NMOCD for site clean up.

Scope of Work for Entombment of Impacted Soils

NOTE: Phoenix, for the purpose of this work plan, will estimate that there is approximately 1,500cyds of impacted cuttings and drilling mud at the site that needs to be addressed for site closure.

- 1. First Phoenix will call One-Call for line spot clearance before any excavation at the site is started.
- 2. Phoenix will mobilize to the site located northwest of Loco Hills, NM equipment and personnel necessary to start and complete the site remediation as required, getting the site back into compliance.
- 3. First the site will be cleared of brush and debris and a staging area set up for site control and safety.



- 4. Phoenix will move the stockpile of soils on the backside of the drilling pit back to allow room to excavate the tomb to hold the contents of the drilling pit. While leaving the top of the impacted soils at a minimum of three feet below grade, the size of the tomb will need to be 125x25x20 and will yield an estimated 2,315cyds of total material and will hold an estimated 1,968cyds of impacted soils.
- 5. Once the tomb area has been excavated it will be lined with 20mil HDPE bottom and a 20mil sewn on top above the impacted soils before backfilling.
- Impacted soils at the site will then be transported and placed in the lined tomb area until the top of the impacted soils are at a minimum of three feet below grade.
- 7. Phoenix will field screen the site during the excavation and once the TPH and CL has dropped below clean up requirements final samples will be taken and sent to a third party lab for analysis.
- 8. Once all of the remediation criteria have been met for site closure and compliance, the site will be backfilled with clean material from the site. The site will be contoured with a slight crown to prevent the ponding of any water and reseeded.
- 9. Once all of the closure criteria have been met, a final closure report will be prepared by Phoenix. This report will include a summary of remediation operations, findings on-site and lab analysis, site maps and project photos.

If you have any questions and/or need more data in regards to this project please call 505-631-8314 at any time.

Sincerely.

Allen Hodge, REM VP Operations Phoenix Environmental LLC

