<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410 **District IV** 1220 S. St. Francis Dr., Santa Fe, NM 87505

1774

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes X No faction. Registration of a pit or below-grade tank Closure of a pit or below-grade tank

	k covered by a "general plan"? Yes X No or below-grade tank Closure of a pit or below-grade	
Type of action Registration of a pit of	it below-grade talk Closure of a pit of below-grad	OCD-ARTESIA
Operator: FOG RESOURCES, INC. Telephone: 432-686-3600 e-mail address:		
Address: P0 Box 2267, Midland TX 79702		
Facility or well name. Niagara 3 Fee Com #1HAPI#: 30-015-36237 U/L or Qtr/Qtr NE Sec 3 T 18S R23E		
	760 FNL Longitude 460	' FEL NAD 1927 ☐ 1983 ☐
Surface Owner: Federal State Private Indian		
Pit	Below-grade tank	
Type. Drilling X Production Disposal	Volume:bbl Type of fluid: Construction material:	
Workover, Emergency		
Lined Dulined	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay		
Pit Volume bbl		
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(Opoints)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(Opoints)
The source, or the state of the	Less than 200 feet	(20 mounts)
Distance to surface water. (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(20 points)
ırrıgation canals, ditches, and perennial and ephemeral watercourses.)	·	(10 points)
	1000 feet or more	(Opoints)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks (2) Indicate disposal location: (check the onsite box if		
your are burying in place) onsite 🔀 offsite 🗌 If offsite, name of facility		
remediation start date and end date. (4) Groundwater encountered No 🕱 Yes 🔲 If yes, show depth below ground surfaceft and attach sample results		
(5) Attach soil sample results and a diagram of sample locations and excavations		
Additional Comments RECLAIM DRILLING PIT PER OCD REGULATIONS. DIG DEEP BURIAL HOLE.		
LINE WITH 12-MIL LINER. MIX ALL CONTENTS IN PIT TO STIFFEN AND PLACE		
IN ENCAPSULATION TRENCH: CAP WITH 20-MILLINER, COVER WITH 3' OR MORE		
TOP SOIL OR LIKE MATERIAL. PULL SAMPLES FROM BOTTOM OF PIT; IF SAMPLES		
PASS, BACKFILL OLD DRILLING PITS WITH CLEAN TOP SOIL.		
Though the Medical Marine Very		
I hereby certify that the information above is true and complete to the best of my knowledge and belief I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .		
Date: 6/06/08 MORGAN TOOLS CO., LLC		
Printed Name/Title Stephen Wilson, Foreman	Signature Stephens U.S.	loon
Your certification and NMOCD approval of this application/closure does not relieve the operator of fiability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval:	J. 1.1 11	
Printed Name/Title	Signature Signed By Mile Bear	www

NOTIFY OCD 24 HOURS PRIOR to beginning closure and 24 HOURS PRIOR to obtaining samples. Samples are to be obtained from pit area and analyses submitted to OCD prior to back-filling.

If burial trench is to be constructed in pit area, samples are to be obtained and analyses submitted to OCD PRIOR to lining trench.