OCD COP9

5

Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No 1004-0137 Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.		5 Lease Senal No NMLC-054988A
		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE- Other inst	ructions on reverse side	7 If Unit or CA/Agreement, Name and/or No
I Type of Well ✓ Oil Well□ □ ☐ Gas Well□□ ☐ Other	MAY 1.5.2008	8 Well Name and No.
2. Name of Operator COG Operating LLC 3a Address 550 W. Texas Ave., Suite 1300 Midland, TX 79701 3b Phone No (include area code) 432-685-4395		
		10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T., R., M., or Survey Description)		Loco Hills; Glorieta-Yeso 96718 11 County or Parish, State
1100' FNL & 2230' FWL Sec 21, T17S, R30E, Unit C		Eddy, NM
12. CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF N	OTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Acidize Deepen Production (Start/Resume) Water Shut-Off Well Integrity Subsequent Report Casing Repair Change Plans Plug and Abandon Temporarily Aband		
determined that the site is ready for final inspection) 02-19-08 MIRU. POOH w/pump, rods. 02-20-08 POOH w/tbg. RIH w/retainer & set @ 4297'. psi w/200 sxs Class C w/2% CaCl2 + 1/4# floo 02-21-08 RIH w/4 3/4" bit. Drill out cmt & retainer. Ci 02-22-08 Drill out cmt f/4299' to 4810'. Drill out shoe ju 02-23-08 Drld cmt & shoe to 4399'. Drld new formation 03-04-08 Depth 6055'. RIH w/ 138 jts 4", 11.3#, L-80 U down @ 4:07 pm CST. Opened stage tool & ci 03-05-08 Tagged DV tool @ 4862'. Drld out DV tool. C 03-28-08 RIH w/perf gun. Perf gun stuck. Fish Perf gun 03-31-08 Perf @ 5610'-5810', 2 SPF, 42 holes. 04-01-08 Acidize w/2500 gal 15%. Frac w/63,000 gal Li plug & set @ 5570. Perf @ 5340'-5540', 2 SPF 04-03-08 Drill on plug for 1 1/2 hr, fell through. Push p 04-07-08 RIH w/composite BP @ 5570'. 04-09-08 RIH w/Pkr & set @ 4605'.	Pump 300 sxs Class C w/2% Cacele + 3 pps gilsonite. Reversed of irc hole clean. Int to 4882'. In f/4907' to 6055'. LTFJ csg. Set @ 6043'. DV tool of irc. 80 sxs to pit. Pumped plug & irc. hole clean. RIH to PBTD @	C12 + 1/4# Flocele + 3 pps gilsonite. Squeeze to 2000 at 70 sxs cmt. @ 4862'. Cmt w/150 sxs Class C cmt + additives. Plug closed DV tool. 5990'. Spot 500 gals 10% acetic acid @ 5980'.
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed) Carol Ann Lance	Title Regulatory	Anglyst
Curor time mante	inc regulatory	annay go

14 Thereby certify that the foregoing is true and correct Name (Printed/Typed)

Carol Ann Lance

Title Regulatory Analyst

Date

O5/01/2008

Title O5/01/2008

Title Date

Approved by

Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

which would entitle the applicant to conduct operations thereon

Berry A Federal #14 API#: 30-015-32279 EDDY, NM

3160-5 (13) ADDITIONAL INFORMATION

- 04-11-08 Perf @ 5340'-5540', 2 SPF, 32 holes. Acidize w/5000 gal 15% HCL. Frac w/122,000 gal lightning 25#; 149,843# 16/30 white sand; Tail-in w/28,958# SiberProp. Flush w/base gel.
- 04-14-08 Release Pkr & POOH.
- 04-15-08 Drill out plug in 2 hrs. Push plug to 5790'.
- 04-16-08 Wash sand to new PBTD @ 5911.
- 04-17-08 RIH w/145 jnts 2 7/8" tbg, SN @ 4766'. RIH w/2-1/2x1-1/2x 16' RHTC pump & rods. Hang well on.