

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505



WELL API NO.
30-015-29623

5. Indicate Type of Lease **FED**
STATE ☐ ~~FEE~~ ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

SandTank 17 Federal Com

8. Well Number

1

9. OGRID Number

10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Samson Resources Company

3. Address of Operator
200 N Loraine St., Ste 1010, Midland, TX 79701

4. Well Location

Unit Letter H : 2310 feet from the N line and 660 feet from the E line
Section 17 Township 18S Range 30E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3501' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/21/2008 -
POH w/ completion assembly
Set CIBP @ 7266'. Dump cmt.
GIH w/ 2/ 3/8" tubing. Tag plug @ 7230'.
Displace hole w/ 9.5 ppg mud.
Ran free point. Casing free @ 3895'.
Perf 5 1/2" casing f/ 4356-58 w/ 4 holes.
Set CR @ 4250'. Squeeze w/ 25 sx. Dump cmt on CR. TOC 4100'.
Perf 4 holes @ 3957'. Set pkr @ 3615' squeeze w/ 100 sx.
Tag plug @ 3785'. Cut and pull 5 1/2" csg @ 3540'. Spot 35 sx plug @ 3600'.
Tag plug @ 3488'. Spot 35 sx plug @ 1486'. Tag @ 1470'. Spot 175 sx. Plug @ 704'.
Spot surface plug @ 30'. Cutoff wellhead. Weld on P & A marker.
P & A 06/05/08. Witnessed by BLM.

ACCEPTED FOR RECORD

SEP 10 2008

Gerry Guye, Deputy Field Inspector
NMOCD-District II ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kenny Krawietz TITLE District Engineer

DATE 09/08/2008

Type or print name Kenny Krawietz

E-mail address: KKrawietz@samson.com

PHONE: 432-686-6337

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):