## Form 3160-5 , (February 2005)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD-A	RTESIA
-------	--------

FORM APPROVED

OMB No. 10	04-0137
Expires: March	n 31, 2007

		_
Lease Serial No.		
	NM100558	

	NOTICES AND REPORTS ON WELLS
	form for proposals to drill or to re-enter an
abandoned well.	Use Form 3160-3 (APD) for such proposals

5, Lease Seliai No.	NM100558	
6. If Indian, Allotte	e or Tribe Name	<del>-</del> "

	orm for proposals to Use Form 3160-3 (A					
SUBMIT IN TRIPLICATE – Other instructions on page 2.		7. If Unit of CA/Agreement, Name and/or No.				
1. Type of Well	11/1 07 2000			8. Well Name and N	0.	
Oil Well Gas W	ell Other	`			RI	ÖX "10" #1
Name of Operator     RKI Exploration	& Production	ocd.	<b>ARTESI</b>	4	9. API Well No. 30	01536210
3a. Address 3817 NW Expresswa Oklahoma City, OK.	ry, Suite 950		(include area cod 949-2221	le)	10. Field and Pool of BRUSHY DR	r Exploratory Area AW DELAWARE - EAST
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) 990 FSL & 330 FWL, Sec. 16-26S-30E			11. Country or Parish, State EDDY COUNTY, NEW MEXICO			
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDI	CATE NATURE	OF NOTIC	E, REPORT OR OT	HER DATA
TYPE OF SUBMISSION	<del></del>		TY	PE OF ACT	ION	
Notice of Intent  ✓ Subsequent Report	Acidize Alter Casing Casing Repair	New (	Production (Start/Resume) are Treat Reclamation  Construction Recomplete		mation mplete	Water Shut-Off  Well Integrity  Other Spud, Surface and Intermediate casing.
Final Abandonment Notice	Change Plans Convert to Injection	☐ Plug 2	nd Abandon Back	_ `	oorarily Abandon r Disposal	memediate casing.
testing has been completed. Final Addetermined that the site is ready for RIG UP. SPUD IN @ 07:00 HRS. OF DRILLED 17-1/2" HOLE TO 811'. RPUMP 29 BBLS. GEL SWEEP, 432 2% S1 + 0.125 pps D130, DENSITY SURFACE. NIPPLE UP BOPE AND DRILLED OUT SHOE 26.5 HOURS DRILLED 11" HOLE TO 3523'. RUN FLUSH, LEAD: 910 SX CLASS "C" RETURNS, CIRC 250 SX OF CEME DRILLED OUT SHOE 22.25 HOURS 14. I hereby certify that the foregoing is tr	Abandonment Notices must be final inspection.)  N 6-16-08.  AN 13-3/8", 68#, J-55, ST SK 35:65 POZ C + 6% D. 14.8 YIELD 1.34 DISPLATEST BOP 250 LOW, 10 AFTER CEMENT IN PLATES S JTS. 8 5/8" CASING, 2W/ ADDS, TAIL: 200 SX CENT TO SURFACE.	e filed only after 8C CASING. 20 + 4pps D24 CE w/ 115 BB 00 HIGH OK. ACE. SHOE@ 3523' CLASS "C" W/	SHOE @ 811', + 0.125pps D1 L. FW BUMP P  . FLOAT COLL ADDS, DISPLA	FLOAT CO 30 + 3% S LUG W/ 47 AR @ 3478 CE W/ 114	DLLAR @ 766'. CEI 1 DENSITY 12.7 Y 10 PSI. HELD CIRC B'. CEMENT W/ SC 1 BBLS FRESH W/	MENT W/ SCHLUMBERGER, IELD 1.94 TAIL: 200 SK CLASS C + CULATED 80 SK OF CEMENT TO CHLUMBERGER, 20 BBL GEL
14. I hereby certify that the foregoing is tr Name (Printed/Typed)  Gene Sin					2008 Production Supe	erintendent
Signature Lune	emu		NMOCD Date	Digitize	Production Super Field Inspector	PTED FOR RECORD
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by  Conditions of approval, if any, are attached						OCT 5 2008
that the applicant holds legal or equitable ti entitle the applicant to conduct operations t	hereon.		N/			MI OF LAND ANADADATAT
Title 18 U.S.C. Section 1001 and Title 43 fectitious or fraudulent statements or repres	U.S.C. Section 1212, make it a sentations as to any matter with	crime for any pe	rson knowingly an	d willfully to	o make to any department	tent on agency of the United States any false ARLSDAU FIELD UFFILE