

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr, Hobbs, NM 87240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

FEB 24 2009

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-00722
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Empire Abo Unit 'L'
8. Well Number 16
9. OGRID Number 00778
10. Pool name or Wildcat Empire Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other
2. Name of Operator BP America Production Company
3. Address of Operator P.O. Box 1089 Eunice NM 88231
4. Well Location Unit Letter <u>P</u> : <u>660</u> feet from the <u>S</u> line and <u>660</u> feet from the <u>E</u> line Section <u>2</u> Township <u>18S</u> Range <u>27E</u> NMPM County <u>Eddy</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3584' RKB
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/> Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/12/09: ND WH, NU BOP. RELEASE PKR. POH LAYING DOWN 192 JTS 2 3/8" TBG.
MOVE OUT OLD TBG. MOVE IN 190 JTS 2 3/8" WORK TBG. PICK UP & RIH W/4 3/4" BIT,
5 1/2" CSG SCRAPER & 60 JTS 2 3/8" TBG.
2/16/09: RIH W/TBG. SCRAPER @ 5938'. POH. RIH W/CIBP ON TBG. SET @ 5920'. LOAD
CSG W/FRESH WATER. TEST CIBP & CSG TO 500 PSI. TEST GOOD.
2/17/09: DISPLACE CSG W/MUD.

Continued on page 2.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Barry C. Price TITLE Area Operations Team Lead DATE 2/24/09
Type or print name Barry C. Price E-mail address: barry.price@bp.com Telephone No. 575-394-1648

For State Use Only

APPROVED BY Pho Harper TITLE _____ DATE 2/25/09
Conditions of Approval, if any: _____

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page and DATE
Forms: www.emnrd.state.nm.us/oed.

Form C-103
Empire Abo Unit L-16
30-015-00722
Continued from Page 1

2/18/09: SPOT 30 SX CMT FROM 5920' TO 5631'. POH LAYING DOWN TBG. BOTTOM OF TBG @ 3379'. SPOT 30 SX CMT FROM 3379' TO 3090'. LAY DOWN 10 JTS TBG. POH W/TBG. WOC. RIH W/SLOTTED SUB ON 2 3/8" TBG. TAG CMT @ 3085'. POH LAYING DOWN TBG.

2/19/09: POH LAYING DOWN TBG. RIG UP KEY WIRELINE. RIH & PERF 5 1/2" CSG @ 1100'. POH & RIG DOWN KEY WIRELINE. PUMP ON 5 1/2" CSG W/FRESH WATER, CIRCULATE OUT 8 5/8" CSG. ND BOP. NU WELLHEAD FLANGE. MIX & PUMP 350 SX CMT, DOWN 5 1/2" CSG. RAN OUT OF CMT W/LIGHT CMT WATER RETURNS OUT 8 5/8" CSG. DISPLACE W/2 BBL FRESH WATER TO GET GOOD CMT RETURNS OUT 8 5/8" CSG. WOC.

2/20/09: RIH W/TBG & TAG @ 320'. LOAD 8 5/8" CSG X 5 1/2" CSG W/1 BBL FRESH WATER. SPOT 35 SX CMT FROM 320' TO SURFACE. POH LAYING DOWN TBG. TOP OFF 5 1/2" CSG W/CMT.

2/23/09: DIG OUT AROUND WELLHEAD. CUT OFF ALL ANCHORS AND WELL HEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, BACKFILL AND LEVEL LOCATION.