

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
MAY 28 2009

WELL API NO. 30-015-35003
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name MARATHON 26 STATE
8. Well Number #19
9. OGRID Number 255333
10. Pool name or Wildcat Red Lake, Queen, Grayburg, San Andres (51300)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3674' GL

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator LIME ROCK RESOURCES A, L.P.	
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401	
4. Well Location Unit Letter A : 330 feet from the NORTH line and 330 feet from the EAST line Section 26 Township 17-S Range 28-E NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3674' GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Open Middle San Andres ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Lime Rock Resources would like to open the middle San Andres (SA) as follows:

TOH w/rods, pump, & tbq. Set 5-1/2" RBP over existing lower SA perfs (3003'-3199') @ 2960'. PT 5-1/2" csg to 500-1000 psi. Perf middle SA at ~2460'-2802'. Breakdown with about 5500 gal 15% NEFE acid. Frac with about 140,000# 16/30 sand in 25# X-linked gel. Swab well. Run tbq, pump, & rods, & pump test middle SA. After pump test, remove RBP & produce middle & lower SA perfs together.

Spud Date: 10/17/06

Drilling Rig Release Date: 10/28/06

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 5/27/09

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: Jaquie Reeves TITLE Geologist DATE 5/29/2009
Conditions of Approval (if any):