

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

JUN - 3 2009

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-34861
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Nadel and Gussman Permian LLC		6. State Oil & Gas Lease No.
3. Address of Operator 601 North Marienfeld, Suite 508, Midland, Texas 79701		7. Lease Name or Unit Agreement Name
4. Well Location Unit Letter <u>C</u> : <u>660</u> feet from the <u>North</u> line and <u>1650</u> feet from the <u>West</u> line Section <u>20</u> Township <u>21-S</u> Range <u>28-E</u> NMPM County <u>Eddy</u>		Bond Fee
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,195 GL		8. Well Number 02
		9. OGRID Number 155615
		10. Pool name or Wildcat Undesignated Atoka

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/28/09 MIRU pulling unit and other equipment. 3/3-4/09 fish rods and tbg 3/5-07 set cmt ret @ 10,784 and sqz off Strawn perfs 10,802-10,812 w\ 150 sxs CI H. Set snd cmt ret @ 10,618' and sqz off perfs 10,708 to 10,748' w 400 sxs. 3/08-11/09 Woc and drill out. 3/12/09 test perfs 10,708-748 will not hold. 3/13/09 Spot 50 sxs cmt across perfs press up to 3500 psi and sdfn. 3/14-16/09 woc. 3/17/09 test sqz to 500 psi test ok. 3/18/09 drill up cmt ret @ 10,784 and test sqz @ 10,802 to 10,812 will not hold. 3/19/09 Spot 17 sxs of CI H and press up to 3500 psi. 3/20-23/09 WOC. 3/24/09 cmt still soft drill out and test perfs no test. 3/25/09 spot 25 sxs cmt across perfs and press up to 3500 psi. 3/26/09 woc. 3/27/09 drill out cmt and test sqz test ok. 3/28/09 clean out to pbtd of 12,182'. 3/29-31/09 no activity. 4/1/09 pu tcp guns and tih spot guns to perf 11,048-11,058'. 4/02/09 drop bar and perforate Atoka. 4/03-06/09 swab and flow test Atoka. 4/07/09 acidize Atoka w/ 2000 gals of 7.5% HCl. 4/08-13/09 swab back and recover load. 4/14-29/09 flow test to sales. 4/30-5/10/09 run BHP buildup. 5/11/09 put back on line.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE K. E. McCready TITLE NM Operations Manager DATE 5/29/2009

Type or print name K. E. McCready E-mail address: kemm@naguss.com PHONE: 432-682-4429
For State Use Only

APPROVED BY: Jaqui Roar TITLE Geologist DATE 6/4/2009
Conditions of Approval (if any):

1

WELL NO.:	2
COUNTY:	Eddy
LEGAL:	Sec 20 T21 S R 28 E
DRAWN BY:	KEM
DATE:	6/15/2007

FIELD.

660 FNL 1650 FWL

SPUD DATE: 6/7/2006

6/7/2006

CONTRACTOR

WELL NO. :

2

COUNTY _____

Eddy

LEGAL:

Sec 20 T21 S R 28 E

DRAWN BY

KEM

DATE _____

6/15/2007

API #

30 - 015 - 34861

STATE

New Mexico

GL

3194

DF

KB

19

Hole Size	Csq Design
1/2"	1/2"
3/4"	3/4"
1"	1"
1 1/4"	1 1/4"
1 1/2"	1 1/2"
1 3/4"	1 3/4"
2"	2"
2 1/2"	2 1/2"
3"	3"
3 1/2"	3 1/2"
4"	4"
4 1/2"	4 1/2"
5"	5"
5 1/2"	5 1/2"
6"	6"
6 1/2"	6 1/2"
7"	7"
7 1/2"	7 1/2"
8"	8"
8 1/2"	8 1/2"
9"	9"
9 1/2"	9 1/2"
10"	10"
10 1/2"	10 1/2"
11"	11"
11 1/2"	11 1/2"
12"	12"
12 1/2"	12 1/2"
13"	13"
13 1/2"	13 1/2"
14"	14"
14 1/2"	14 1/2"
15"	15"
15 1/2"	15 1/2"
16"	16"
16 1/2"	16 1/2"
17"	17"
17 1/2"	17 1/2"
18"	18"
18 1/2"	18 1/2"
19"	19"
19 1/2"	19 1/2"
20"	20"
20 1/2"	20 1/2"
21"	21"
21 1/2"	21 1/2"
22"	22"
22 1/2"	22 1/2"
23"	23"
23 1/2"	23 1/2"
24"	24"
24 1/2"	24 1/2"
25"	25"
25 1/2"	25 1/2"
26"	26"
26 1/2"	26 1/2"
27"	27"
27 1/2"	27 1/2"
28"	28"
28 1/2"	28 1/2"
29"	29"
29 1/2"	29 1/2"
30"	30"
30 1/2"	30 1/2"
31"	31"
31 1/2"	31 1/2"
32"	32"
32 1/2"	32 1/2"
33"	33"
33 1/2"	33 1/2"
34"	34"
34 1/2"	34 1/2"
35"	35"
35 1/2"	35 1/2"
36"	36"
36 1/2"	36 1/2"
37"	37"
37 1/2"	37 1/2"
38"	38"
38 1/2"	38 1/2"
39"	39"
39 1/2"	39 1/2"
40"	40"
40 1/2"	40 1/2"
41"	41"
41 1/2"	41 1/2"
42"	42"
42 1/2"	42 1/2"
43"	43"
43 1/2"	43 1/2"
44"	44"
44 1/2"	44 1/2"
45"	45"
45 1/2"	45 1/2"
46"	46"
46 1/2"	46 1/2"
47"	47"
47 1/2"	47 1/2"
48"	48"
48 1/2"	48 1/2"
49"	49"
49 1/2"	49 1/2"
50"	50"
50 1/2"	50 1/2"
51"	51"
51 1/2"	51 1/2"
52"	52"
52 1/2"	52 1/2"
53"	53"
53 1/2"	53 1/2"
54"	54"
54 1/2"	54 1/2"
55"	55"
55 1/2"	55 1/2"
56"	56"
56 1/2"	56 1/2"
57"	57"
57 1/2"	57 1/2"
58"	58"
58 1/2"	58 1/2"
59"	59"
59 1/2"	59 1/2"
60"	60"
60 1/2"	60 1/2"
61"	61"
61 1/2"	61 1/2"
62"	62"
62 1/2"	62 1/2"
63"	63"
63 1/2"	63 1/2"
64"	64"
64 1/2"	64 1/2"
65"	65"
65 1/2"	65 1/2"
66"	66"
66 1/2"	66 1/2"
67"	67"
67 1/2"	67 1/2"
68"	68"
68 1/2"	68 1/2"
69"	69"
69 1/2"	69 1/2"
70"	70"
70 1/2"	70 1/2"
71"	71"
71 1/2"	71 1/2"
72"	72"
72 1/2"	72 1/2"
73"	73"
73 1/2"	73 1/2"
74"	74"
74 1/2"	74

12-1/4" hole
9-5/8", 40#
N-80, LT&C
Set @ 2890'
Cmt w/ 1197 sxs
Circ

DV Tool @ 8217'

5-1/2", 17#
P-110 LT&C
8-3/4" Hole
Cmt w/ 1930 sxs
Toc Unk

All depths include 12.47' of KB

TUBING DETAILS

ITEM	NOM OD in	PPF	GRD	MAX OD	MIN ID	LENGTH	BTM DEPTH
1 2-7/8 " tbq 350 jts	2.875	6.5			2.441		
2 2.25 F on/off tool					2.25		
3 Bkr hornet pkr	4.625				2.441		10959.0
4 10' 2-7/8 Sub	2.875				2.441		
5 2.25 F nipple	2.875				2.25		
6 10' 2-7/8 sub	2.875				2.441		
7 2.25 RN	2.875				2.197		
8 WLREG					2.441		10990.0
8							
9							
10							
11							
12							
13							
14							
15							

Strawn Perfs

Chert

10,706-10,748

4 spf 168 holes sqz w/ 450 sxs

Sand

10,802-10,812

6 spf 60 holes

Sqz wł 175 sxs

ATOKA PERFS

11.050'-11.058' and 11.064'-11.072'

PBTD @ 12,182'

TD @ 12,270'