

	1	
State of New Mexico	Form C-103	
Office District i Energy, Minerals and Natural Resources	AUG 10 2009 June 19, 2008	
1625 N French Dr , Hobbs, NM 88240	WELL API NO.	
District II 1301 W Grand Ave, Artesia, NM 88210 OIL CONSERVATION DIVISION	30-005-63778	
District III 1220 South St. Francis Dr. 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE X FEE	
District IV Santa Fe, NM 87505	6 State Oil & Gas Lease No	
1220 S St Francis Dr , Santa Fe, NM 87505	VA-2355	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Dehavilland State	
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		
1 Type of Well. Oil Well Gas Well X Other	8. Well Number 1	
2 Name of Operator	9. OGRID Number	
Lime Rock Resources A, L P 3. Address of Operator	255333 10. Pool name or Wildcat	
Heritage Plaza, 1111 Bagby St. Suite 4600, Houston, TX 770		
4 Well Location		
Unit Letter <u>E. 1,980</u> feet from the <u>North</u> line and 660 feet from the <u>West</u> line		
Section 28 Township 5S Range 26E	NMPM Chaves County	
11 Elevation (Show whether DR, RKB, RT, GR,	etc)	
3,835' GR		
12 OL 1 A	Provide Oil Did	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO:	UBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL W		
-	DRILLING OPNS P AND A X	
PULL OR ALTER CASING	IENT JOB	
DOWNHOLE COMMINGLE		
OTHER OTHER		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work) SEE RULE 1103. For Multiple Completions. Attach wellbore diagram of proposed completion or recompletion.		
of recompletion.		
<u>07/14/2009:</u>		
TIH with tubing and tagged CIBP at 5,515'. Loaded hole with mud.	1, 6, 1	
Spotted 25 sxs cement from 4,126' to 3,832' (across the top of the Abo). WOC. Tagged top of plug		
Spot 25 sxs cement from 1,834' to 1,720' (above open San Andres perforations). WOC. 07/15/2009:		
Spotted 25 sxs cement from 958' to 687'. Tagged top of plug		
Spotted cement plug from 60' back to surface.		
Cut off wellhead and install dry hole marker Cut off anchors, fill in cellar, and restore location.		
Cut off anchors, fill in centar, and restore location.		
Well P&A'd on 07/15/2009.		
Work witnessed by Phil Hawkins - NM OCD Representative.		
I hereby certify that the information above is true and complete to the best of my knowledge.	edge and belief	
2 1 10:11		
SIGNATURE TITLE Vice President - Open	rations DATE: 03 August 2009	
Type or print name <u>C. Tim Miller</u> E-mail address: <u>tmiller@limerockresources.com</u> PHONE. <u>(713) 292-9514</u>		
For State Use Only Approved for plugging of well bore only.		
Liabil to under bond for	retained pending receipt C//C/	
APPROVED BY: TITLE of C 103 (Sursequent R which may be found at the conditions of Approval (if any):	Report of Well Plugging) DATE 0/8/00/00/00/00/00/00/00/00/00/00/00/00/	
Forms, www.cmnrd.stat		





FINAL ABANDONMENT



Spotted 25 sxs cement from 958' to 687' (tagged top of plug)

TOC @ 1,350'

Spotted 25 sxs cement from 1,834' to 1,720'

San Andres Perfs. 1,870-72' (18 – 0.42" DIA holes)

Spotted 25 sxs cement from 4,126' to 3,832' (tagged top of plug)

<u>Zone</u>	<u>Top</u>
Seven Rivers	198'
Queen	526'
Grayburg	704'
San Andres	910'
Glorieta	1,964
Tubb	3,484'
Abo	4,154

CIBP @ 5,515' w/ 35'c ement on top (EXISTING)

<u>Cisco Perfs</u> 5,565-73' (18 – 0 41" DIA holes)

CIBP @ 5,846' w/ 35' cement on top

Strawn Perfs 5,896-01', 5,905-16', 5,922', 5,928'; 5,954', 5,965' & 5,976-84' (184 - 0 42" DIA holes)

CIBP @ 6,044' w/ 35' cement on top <u>Siluro-Devonian Perfs</u> 6,094-37' (88 – 0 42" DIA holes)

4-1/2", 11 6#, L-80 & N-80, LT&C Casing @ 6,250'

TD @ 6,250'

PBTD @ 6,205'

Lime Rock Resources Dehavilland State Unit 1 Sec 28E-5S-26E Chaves County, NM