Submit 3 Copies To Appropriate District Office District I •	State of New Mexico Energy, Minerals and Natural Resources	Form C-103 Revised June 10, 2003
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-015-33038
District III	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	•	
SUNDRY NOTICE	ES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Ribbon BDR
PROPOSALS.)		8. Well Number
1. Type of Well:	Other	1
Oil Well Gas Well X 2. Name of Operator	Other RECEIVED	9. OGRID Number
Yates Petroleum Corporation	JAN 0 1 2004	9. OGRID Number 025575
3. Address of Operator		10. Pool name or Wildcat
105 S. 4 th Street, Artesia, NM 8	8210 OCD-ARTESIA	Chester
4. Well Location		
Unit Letter E : 1650	0 feet from the North line and 9	90 feet from the West line
Section 33	Township 18S Range 26E	NMPM <u>Eddy</u> County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3388'GR		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTE		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK []	PLUG AND ABANDON REMEDIAL WOR	K ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DR	ILLING OPNS. PLUG AND ABANDONMENT
	MULTIPLE CASING TEST A CEMENT JOB	
OTHER:	☐ OTHER: Spud, s	surface and intermediate casing X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion		
or recompletion.		
12/19/03 – Spudded well. Set 40' of conductor. 12/26/03 – Resumed drilling at 8:00 AM. Set 13-3/8" 48# casing at 550'. Cemented with 600 sx "C" with additives. Cement circulated		
to surface. WOC 21 hrs 45 mins. Reduced hole to 12-1/4" and resumed drilling.		
12/28/03 - Set 9-5/8" 36# casing at 1212'. Cemented with 185 sx 35:65:6 with additives. Tailed in with 200 sx "C" with additives.		
	ent to surface with 225 sx Class "C" Neat. WOC 39	hrs 30 mins. Reduced hole and resumed
drilling.		
71 1 (6 1 1 1 6 1 1		
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE:	TITLE: Regulatory Compliance	Supervisor DATE: December 31, 2003
Type or print name Ting Huerta	E-mail address: tinah@ypc	nm.com Telephone No. 505-748-1471
(This space for State and	www. Bum Districts	Expervisor JAN 5 2003
APPPROVED B	TITLE	DATE
Conditions of approval, if any:		