Form 3160-5 (September 2001)

UII CONS.

N.M. DIV-Dist. 2

UNITED STATES 1301 W. Grand Avenue
DEPARTMENT OF THE INTERIOR RICESIA, NM 88210
BUREAU OF LAND MANAGEMENT AREA

BUREAU OF LAND MANAGEMENT AR

FORM APPROVED OMB No. 1004-0135 Expires: January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

5. Lease Serial No. NM - 24160

abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side					6. If Indian, Allottee or Tribe Name			
					7. If Unit or	7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well						PARKWAY DELAWARE UNIT		
✓ Oil Well ☐ Gas Well ☐ Other						8. Well Name and No.		
2. Name of Operator					-	PDU # 510		
ST. MARY LAND & EXPLORATION						9. API Well No.		
3a. Address 3b. Phone No. (incl RECEIVED					30-015-33072			
				CIVEO		10. Field and Pool, or Exploratory Area		
PO BOX 7168 BILLINGS, MO		(406) 245-6	,248 JAN (7084	_1	AY DELAWAR	•	
4. Location of Well (Footage, Sec., T, R., M., or Survey Description) 1870' FSL & 1480' FEL UL: J			OCD-ARTESIA			11. County or Parish, State		
SEC. 35 - T19S -R29E					EDDY, N	EDDY, NM		
12. CHECK API	PROPRIATE BOX(ES) TO	INDICATE	NATURE (OF NOTICE, R			ГА	
TYPE OF SUBMISSION	<u> </u>	TYPE OF ACTION						
_	☐ Acidize ☐ Deepen ☐ Production (Start/Resum				t/Resume)	ne) Water Shut-Off		
Notice of Intent	Alter Casing	Fracture T	reat		,	Well Integri	ity	
Subsequent Report	Casing Repair	New Cons	truction	Recomplete		_	d, Surface & Int.	
Subsequent Report	Change Plans	Plug and A	Abandon 🗍	Temporarily Ab	andon		ement Details	
Final Abandonment Notice	Convert to Injection	Plug Back						
11/29-30/03 Ran 13 3/8" 48# H-4 Texas Pattern Shoe, Cement with 250 sx Temp Survey TOC = 12/5-6/03 Ran 8 5/8" intermedi FS (1'); 1 jt 32# J-55 J55 STC (1577.95'). Cement 1st stage wit Drop bomb and open Cement 2nd stage wi Circulated 220 sx to	rface hole at 11:30 am. 40 STC surface casing as follo 1 jt csg, Float Insert, 7 jts. cas H+ 10%A-10+.25#CF+ 1%=193'. Cement 3 stages with 1 late casing as follows: STC (44.42'); FC (1.35') 17 jts. Shoe set at 3200'. th 350 sx 50:50:10 + 5#salt + 1 DV. Did not circulate cement th 800 sx 50:50:10 + 5#salt + surface.	ing. Set at 341 CaCl2 + 10# J ", total 150 sx s 32# J55 STC /4#CF + .4%S on first stage.	LCM lead and "C" + 3% Ca6 (757.76'); 18 SMS +5#LCM	Cl, to 78'. Cemen jts. 24# J55 STC 1 lead and 200sx	(812.35') Pk: "C" +2% Ca	vith 8 yds ready r-DV tool (18.5') Cl tail. aCl tail.	mix.	
14. I hereby certify that the foregoin Name (PrintedlTyped)	g is true and correct							
HERB THACKERAY			Title OPERATIONS ENGINEER		EER	DEC 3 0 2003		
Signature Aubert	2 Thackeray		Date 12/19/0	03		AL EVICE	acs	
	THIS SPACE F	OR FEDERA	A ASS TRACT TO A STATE OF THE STATE OF	TVI IV. SV. SV. SV. SV. SV. SV. SV. SV. SV. S		PETROLEUM	JENGINE R	
Approved by (Signature)			Name (Printed/Typed)			Title		
Conditions of approval, if any, are attached. Approval of this notice does no certify that the applicant holds legal or equitable title to those rights in the swhich would entitle the applicant to conduct operations thereon.			ant or lease Office			Date		
Title 18 U.S.C. Section 1001 and Tit States any false, fictitious or fraudule	tle 43 U.S.C. Section 1212, make ent statements or representations as	it a crime for ar s to any matter v	ny person know vithin its jurisdic	ingly and willfully	to make to any	y department or ag	ency of the United	