

Office

Energy, Minerals and Natural Resources

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

## OIL CONSERVATION DIVISION

FEB 25 2011 South St. Francis Dr.

Santa Fe, NM 87505

-amended-

WELL API NO.

30-015-36532

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

Quick Draw 15 I

8. Well Number

1

9. OGRID Number

14744

10. Pool name or Wildcat

N. Seven Rivers; Glorieta Yeso 97565

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter I : 1650' feet from the South line and 330' feet from the East line

Section 15 Township 20S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3429' GL

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER:

☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: Completion Sundry

☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/23/09 Run GR & CCL. PBTD @ 3190'. Perforate Lower Yeso @ 2882' - 2896'. 2SPF 14', 28 holes, 0.40" EHD 120° phasing, 19 GC.

10/24/09 Acidize perfs @ 2882' - 2896 w/2500 gal 15% HCl NeFe & 50 ball sealers. Swab test.

10/27/09 Set temporary isolation plug @ 2850'. Perforate Yeso @ 2639' - 2764', 1SPF 25', 25 holes, 0.40" EHD 120° phasing, 19 GC.

10/30/09 Frac perfs @ 2639' - 2764' with 1000 gals 10% HCl, & 50000 gals 20# slickwater carrying 25000# 20/40 Sand. Flowback for cleanup.

10/31/09 RIH w/tbg to 2632'. RIH w/2" x 1 1/4" x 16' THBC pump & rods. Put well on production.

RIH w/2 3/8" 4.6# J55 tbg to 2632'.

Spud Date: 09/30/09

Rig Release Date: 10/06/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 11/09/09

Type or print name Jackie Lathan E-mail address: jlathan@Mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 2-15-2010

Conditions of Approval (if any):