

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-37618

5. Indicate Type of Lease

STATE FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: ☒ Oil Well Gas Well Other

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270 Hobbs, NM 88240

4. Well Location

Unit Letter K : 1650 feet from the S line and 1650 feet from the W line

Section 17 Township 19S Range 26E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3381' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB

OTHER: Completion Sundry

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/21/10 Perforate Yeso @ 3324' - 3398' 1 SPF, 20', 20 holes, 0.40" EHD 120° phasing, 19 GC.

04/22/10 Frac with 1000 gals 10% NEFE Acid with 100,000 gals 20# slickwater & 50000# 20/40 White sand. Set plug @ 3190'. Perforate Yeso @ 2886' - 3066' 1 SPF, 25', 25 holes, 0.40" EHD 120° phasing, 19 GC. Frac Yeso w/1000 gal 10% HCl & 300,000 gal 20# slickwater carrying 150,000# 20/40 White sand. Flowback for cleanup.

04/27/10 MIRU completion unit. Drill out plug @ 3190'. Clean out to 3670' PBTD. RIH with 2 3/8" 4.7# J55 tbg to 3522'

04/28/10 RIH w/2" x 1 1/2" x 20' RHBC pump & rods.

05/14/10 Changed pump to 2 3/8" x 4 1/2" PCP set @ 2874'.

05/17/10 Put well on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 05/19/10

Type or print name Jackie Lathan

E-mail address: jlathan@mewbourne.com

Telephone No. 575-393-5905

For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 6-1-10

Conditions of Approval (if any):