

Submit 1 Copy To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 October 13, 2009

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-28181
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name West Red Lake Unit
8. Well Number 42
9. OGRID Number 6137
10. Pool name or Wildcat San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3290' KB; 3282' GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Devon Energy Production Company, LP

3. Address of Operator
20 North Broadway, Oklahoma City, OK 73102 405.552.4615

4. Well Location
 Unit Letter O _____ : 330 _____ feet from the South _____ line and 1650 _____ feet from the East _____ line
 Section 7 Township 18S Range 27E NMPM County Eddy


12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input checked="" type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Plug & Abandonment

- 8/23/10: MIRU. TIH and tagged CIBP @ 1047'. (San Andres perms from 1072' to 1890')
- Circulate hole with 120 sx cement from CIBP to surface.
- 9/9/10: Cut wellhead off and set dry hole marker. Wellbore plugged & abandoned.



Spud Date: Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack TITLE Operations Technician DATE 9-10-10

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com PHONE: 405.552.4615

APPROVED BY: [Signature] TITLE Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms. www.cmrnd.state.nm.us/oed. DATE 9/15/2010

Conditions of Approval (if any):

Oct

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: WEST RED LAKE UNIT #42		Field: RED LAKE	
Location: 330' FSL & 1650' FEL; SEC 7-T18S-R27E		County: EDDY	State: NM
Elevation: 3290' KB; 3282' GL; 8' KB-GL		Spud Date: 1/28/95	Compl Date: 3/6/95
API#: 30-015-28181	Prepared by: Ronnie Slack	Date: 9/10/10	Rev:

WELBORE PLUGGED & ABANDONED
9/9/10

1. Cut wellhead off 3' BGL.
2. Set dry hole marker. (9/9/10)

17-1/2" hole
13-3/8", 48#, H40, STC, @ 174'
Cmt'd w/300 sx + topped out w/ready mix to surface

12-1/4" Hole
8-5/8", 24#, J55, @ 900'
Cmt'd w/450 sx to surface

1. Tagged CIBP @ 1047'.
2. Displaced hole w/120 sx cement to surface. (8/25/10)

SAN ANDRES PERFED INTERVAL

1072' - 1086' (5/95) Sqzd w/75 sx (3/99) →

1477' - 1596' (5/95)

1645' - 1696' (3/95)

1713' - 1794' (3/95)

1836' - 1846' (3/95)

1852' - 1890' (3/95)

CIBP @ 1047' (7/27/06)

7-7/8" Hole
5-1/2", 15.5#, J55, @ 2008'
Cmt'd w/350 sx to surface

1920' PBTD

2,010' TD

