

Submit 1 Copy To Appropriate District
Office
District I
1625 N French Dr , Hobbs, NM 88240
District II
1301 W Grand Ave , Artesia, NM 88210
District III
1000 Rio Brazos Rd , Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-61170
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Acme
8. Well Number 7
9. OGRID Number 025575
10. Pool name or Wildcat Undesignated; Abo
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3668' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter G : 1780 feet from the North line and 1980 feet from the East line
Section 30 Township 8S Range 26E NMPM Chaves County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/17/10 - NU BOP. Set a CIBP at 4157'. Pumped 57 bbls. Loaded and tested casing to 1000 psi, good
9/20/10 - Pumped 25 sx Class "C" cement on top of CIBP at 4157'. Loaded hole with mud WOC 2 hrs. Tagged cement plug at 3847' Pumped 25 sx Class "C" cement at 1475'. TOC at 1104' Did not have to tag.
9/21/10 - Perforated 4 holes at 890' Broke circulation up 4-1/2" x 8-5/8". Pumped 40 sx Class "C" cement with 3% Cal. Displaced cement down to 660'. WOC 2 hrs Tagged plug at 690'. Perforated 4 holes at 60'. Pumped 15 sx Class "C" cement up 4-1/2" x 8-5/8" to surface. ND BOP
9/27/10 - Dug up cellar and cut off wellhead Installed dry hole marker Filled cellar back in and dug up anchors. Cleaned location WELL IS PLUGGED AND ABANDONED.



Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE September 28, 2010

Type or print name Tina Huerta E-mail address: tnah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Approved for plugging of well under DATE 9/30/2010

Conditions of Approval (if any):

Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.

OK