

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Oil Cons.
N.M. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

J. C. Williamson

3. Address and Telephone No.

P.O. Box 16, Midland, TX 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 660' FEL
Sec. 34, T-26S, R30E

RECEIVED

FEB 20 2004

OCD-ARTESIA

5. Lease Designation and Serial No.
NM-0554499

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross Draw #16

9. API Well No.

30-015-26046

10. Field and Pool, or Exploratory Area

Und. Ross Draw Delaware

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Notify BLM prior to moving in.
2. Set 5-1/2' CIBP @ 4850', cap w/ 35' of cmt. (Note: Top perf @ 4910').
3. Circulate hole clean w/MLF.
4. Perf & sqz 5-1/2' csg. @ 3343' to 3243' w/ 35 sx, WOC & tag.
5. Cut & pull 2000' of 5-1/2" csg.
6. Spot 35 sx 50' inside & outside of 5-1/2" csg. stub, WOC & tag.
7. Perf & sqz 8-5/8" csg. @ 615' to 515', WOC & tag.
8. Perf 8-5/8" csg. @ 60' circulate cement inside & outside to surface.
9. RDMO. Cut off wellhead & anchors, install dry hole marker, & clean location.

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS ATTACHED

APPROVED

FEB 18 2004

14. I hereby certify that the foregoing is true and correct

Signed

Title Agent

(This space for Federal or State office use)

LES BABYAK
PETROLEUM ENGINEER 2-1 -04

Approved by

Title

Date

Conditions of approval, if any: