	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Resources	October 13, 2009
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-015-38082 5. Indicate Type of Lease
District III	1220 South St. Francis Dr.	STATE STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		VO-7638
	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Cassiopeia BQD State Com
DIFFERENT RESERVOIR. USE "APPL PROPOSALS.)	ICATION FOR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
1. Type of Well: Oil Well	Gas Well Other	1H
2. Name of Operator		9. OGRID Number
Yates Petroleum Corporation		025575
3. Address of Operator	27.6	10. Pool name or Wildcat
105 South Fourth Street, Artesia,	NM 88210	Hay Hollow; Bone Spring
4. Well Location		
Surface B : _ B	200 feet from the North line and North Line and	2130 feet from the East line 2130 feet from the East line
Surface - Section 25	Township 26S Range 27E	NMPM Eddy County
BHL - Section 24	Township 26S Range 27E	NMPM Eddy County
The second of the second	11. Elevation (Show whether DR, RKB, RT, GR, et	
ANTONIA (ANTONIA ANTONIA	3095'GR	and the second s
12 Charle	Ammonriate Day to Indicate Nature of Nation	Donart or Other Date
12. Check	Appropriate Box to Indicate Nature of Notice	e, Report of Other Data
NOTICE OF I	NTENTION TO: SU	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK] PLUG AND ABANDON 🗌 REMEDIAL WO	RK ALTERING CASING
TEMPORARILY ABANDON	1	RILLING OPNS.☐ P AND A ☐
PULL OR ALTER CASING		NT JOB
DOWNHOLE COMMINGLE		}
OTHER:	OTHER: Surface	re and Intermediate casing
OTHER: 13. Describe proposed or com		ce and Intermediate casing
13. Describe proposed or com	OTHER: Surfaction operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple C	and give pertinent dates, including estimated date
13. Describe proposed or com	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple C	and give pertinent dates, including estimated date
13. Describe proposed or com of starting any proposed v proposed completion or re	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.	and give pertinent dates, including estimated date ompletions: Attach-wellbore-diagram of RECEIVED
13. Describe proposed or come of starting any proposed very proposed completion or results of the starting and continuous starting and starting and starting and starting and starting and starting are starting as the starting and starting are starting as the starting are starti	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion. The details are all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Cocompletion.	and give pertinent dates, including estimated date ompletions: Attach-wellbore diagram of
13. Describe proposed or comof starting any proposed very proposed completion or results of the second starting any proposed very proposed completion or results of the second starting and second starting and second seco	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple C ecompletion. Audit to drill directionally. and resumed drilling.	and give pertinent dates, including estimated date ompletions: Attach-wellbore diagram of RECEIVED JAN 04 2011
13. Describe proposed or comof starting any proposed we proposed completion or result of the second starting any proposed with the second starting any proposed with the second starting and second starting starting and second starting starting starting and second starting s	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple C ecompletion. Audit to drill directionally. and resumed drilling. e to 11,340°.	and give pertinent dates, including estimated date ompletions: Attach-wellbore diagram of RECEIVED JAN 04 2011 NMOCD ARTESIA
13. Describe proposed or comof starting any proposed was proposed completion or result of the second starting any proposed was proposed completion or result of the second starting and second starting starting starting and second starting	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple C ecompletion. Audit to drill directionally. and resumed drilling.	ar at 11,292'. Cemented stage including estimated date ompletions: Attach-wellbore diagram of RECEIVED JAN 04 2011 NMOCD ARTESIA ar at 11,292'. Cemented-stage-I-with-1015-sx
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous cont	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to 11,340°. O L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 DV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "C	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous cont	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to to 11,340°. 10 L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous cont	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to 11,340°. O L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 DV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "C	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous cont	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to 11,340°. O L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 DV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "C	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous completion. The starting of the startin	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to 11,340°. O L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 DV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "C	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or come of starting any proposed or proposed completion or results of the starting any proposed or proposed completion or results of the starting and continuous completion. The starting of the startin	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. and resumed drilling. to 11,340°. O L-80 casing at 11,340°. DV tool at 5509°. Float coll D174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 DV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "C	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or comof starting any proposed was proposed completion or result of the second starting any proposed was proposed completion or result of the second starting and second starting starting and second starting	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. And resumed drilling. Be to 11,340°. Conductory of the control of	ar at 11,292'. Cemented-stage-l-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 +
13. Describe proposed or comof starting any proposed was proposed completion or resulting the starting any proposed was proposed completion or resulting to the starting and continuous starting to the starting that the starting and starting and starting the starting and starting	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. Auditional directionally. But to drill directionally. But to 11,340°. But to 11,340°. But to 11,340°. But to 11,340°. But to 12,340°. But to 12,340°. But to 13,340°. But to 13,340°. But tool at 5509°. Float coll but to 15,340°. But tool at 5509°. Float coll but to 15,340°. But tool at 5509°. Float coll but to 15,340°. But tool at 5509°. Float coll but to 15,340°. But tool at 5509°. Float coll but to 15,340°. But to 11,340°. But	ar at 11,292'. Cemented-stage-I-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'.
13. Describe proposed or comof starting any proposed was proposed completion or result of the second starting any proposed was proposed completion or result of the second starting and second starting starting and second starting	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. And resumed drilling. Be to 11,340°. Conductory of the control of	ar at 11,292'. Cemented-stage-I-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'.
13. Describe proposed or com	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. And resumed drilling. Be to 11,340°. Conductory of the control of	ar at 11,292'. Cemented-stage-I-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'.
13. Describe proposed or com	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. And to drill directionally. And resumed drilling. Be to 11,340°. Conduction of the control of	ar at 11,292'. Cemented-stage-I-with-1015-sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'.
13. Describe proposed or com	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. And to drill directionally. And resumed drilling. Be to 11,340°. Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. And the state of the state	ar at 11,292'. Cemented stage - with 1015 sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'.
13. Describe proposed or comof starting any proposed variety proposed completion or results. Signature 12/3/10 – KOP at 5806' and continuous 12/6/10 – Reduced hole to 8-1/2" at 12/10/10 – Reached TD 8-1/2" hole 12/11/10 – Set 5-1/2" 17# HCP-11 PVL + 22.5#/sx D151 + 0.375/sx If sx to pit. Circulated 15 sx off of D 27.65#/sx D132 + 5.325#/sx D20 + 11/17/ Spud Date: 11/17/	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. Auditional to drill directionally. Audit resumed drilling. Be to 11,340°. OL-80 casing at 11,340°. DV tool at 5509°. Float collustry to 15 to 15 to 174 + 0.15 to 18 to 19 t	ar at 11,292'. Cemented-stage-l-with-1015 sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'. 12/13/10 Indicate the design of the complex of the
13. Describe proposed or comof starting any proposed variety proposed completion or results. Solve the starting any proposed variety proposed completion or results. Solve the starting any proposed variety proposed variety. Solve to proposed completion or results. Solve to proposed the solve the starting any proposed variety. Solve to proposed variety and solve the	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. Auditional to drill directionally. Audit resumed drilling. Be to 11,340°. OL-80 casing at 11,340°. DV tool at 5509°. Float collustry to 15 to 15 to 174 + 0.15 to 18 to 19 t	ar at 11,292'. Cemented-stage-l-with-1015 sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15 "+ 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'. 12/13/10 Indicate the design of the complex of the
13. Describe proposed or comof starting any proposed was proposed completion or result of the proposed completion of result of the proposed completion of results of results of the proposed completion of results of the proposed completion of results of the proposed completion of results of results of the proposed completion of results of results of the proposed completion of results	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Clecompletion. And the drill directionally. And resumed drilling. Be to 11,340°. Conducted to L-80 casing at 11,340°. DV tool at 5509°. Float coll 20174 + 0.15#/sx D46 + 0.375#/sx D79 + 0.3#/sx D112 EV tool. Cemented stage 2 with 510 sx 35:65:6 Poz "Clearly tool. Cemented stage 2 with 510 sx 35:65:6 Poz "Clearly tool. The state of the best of my knowled and above is true and complete to the best of my knowled to the best of my knowled and the state of the state	ar at 11,292'. Cemented stage - with 1015 sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'. 12/13/10 12/13/10 December 30, 2010 um.com PHONE:575-748-4168
13. Describe proposed or comof starting any proposed variety proposed completion or results. Solve the starting any proposed variety proposed completion or results. Solve the starting any proposed variety proposed variety. Solve to proposed completion or results. Solve to proposed the solve the starting any proposed variety. Solve to proposed variety and solve the	apleted operations. (Clearly state all pertinent details, a work). SEE RULE 19.15.7.14 NMAC. For Multiple Completion. Auditional to drill directionally. Audit resumed drilling. Be to 11,340°. OL-80 casing at 11,340°. DV tool at 5509°. Float collustry to 15 to 15 to 174 + 0.15 to 18 to 19 t	ar at 11,292'. Cemented stage - with 1015 sx + 0.6#/sx D800 (yld 1.81, wt 13). Circulated 15" + 0.887#/sx D112 + 0.125#/sx D130 + /sx D42 (yld 2.08, wt 12.6). Calc TOC at 2380'. 12/13/10 12/13/10 December 30, 2010 um.com PHONE:575-748-4168