Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD	Artesia

FORM APPROVED 0

OMB NO. 1004- Expires: July 31,	
5. Lease Serial No. NMLC029426B	

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side.			6. If Indian, Allotte	If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.	
			7. If Unit or CA/Ag		
Type of Well ☐ Gas Well ☑ Otl	her: INJECTION		8. Well Name and N H. E. WEST B		
Name of Operator Contact: NANCY FITZWATER LINN OPERATING INC E-Mail: nfitzwater@linnenergy.com			9. API Well No. 30-015-27111	9. API Well No. 30-015-27111	
3a. Address 600 TRAVIS SUITE 5100 HOUSTON, TX 77002		3b. Phone No. (include area coo Ph: 281-840-4266 Fx: 281-840-4006	de) 10. Field and Pool, GRAYBURG		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or Paris	11. County or Parish, and State	
Sec 3 T17S R31E 1972FSL 2078FWL			EDDY COUN	EDDY COUNTY, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION		ТҮРЕ (TYPE OF ACTION		
Notice of Intent	☐ Acidize	Deepen .	Production (Start/Resume)	Water Shut-Off	
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity	
Final Abandonment Notice	☐ Casing Repair ☐ Change Plans	New ConstructionPlug and Abandon	☐ Recomplete ☐ Temporarily Abandon	Other	
I mai / toured mineral reduce	Convert to Injection	Plug Back	Water Disposal		
following completion of the involved testing has been completed. Final Al determined that the site is ready for f Re-delivery Notice 3/9/11 Flowed back solids, pu well at 150 BWPD injection ra	TACHED FOR	sults in a multiple completion or re ed only after all requirements, incl	JA. Required subsequent reports shall completion in a new interval, a Form 3 uding reclamation, have been complete acid job and set	160-4 shall be filed once d, and the operator has	
Name (Printed/Typed) TAMMY S	Electronic Submission #1 For LINN O	TENATING INC., Selle to the t	ell Information System Carlsbad ADMIN III	•	
Signature (Electronic S	Submission	Date 03/24/	/2011		
Organica (Electronic C		PR FEDERAL OR STATE		04/06/2011	
Approved By DNM	lettock of	Title LP	E7	Date 4/8/11	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to condition	uitable title to those rights in the	not warrant or	-0		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Conditions of Approval

LINN OPERATING INC

APRIL 08, 2011

- 1. Conduct a Mechanical Integrity Test of the tubing/casing annulus any time the packer or tubing is pulled.
 - a. The test pressure should be 500 psig, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing/reservoir pressure may need to be reduced). Trap that pressure and record it on a chart for 30 minutes. Document the MIT on a calibrated recorder chart within 25 to 85 per cent of its full range.
 - b. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - c. Less than a 10% leakoff may not restrict injection approval. Any leak-off will be evaluated.
 - d. Submit the recorded MIT chart with a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification.
 - e. Descriptions of tubing, on/off equipment, profile nipple installation, and packer setting depth are required. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. **Include the original and three copies of the recorded chart and Sundry** (the original will be returned to the operator).
- 2. Submit the NMOCD permit number and its approved maximum tubing injection pressure.
 - a. Approved injection pressure compliance is required.
 - b. Display real time tubing pressure values onsite. A bourdon tube gauge registering 25% to 85% of its full range is acceptable.
 - c. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - d. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
 - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmosphere pressure. Installation of equipment that will display on site, open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - c. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsig. Notify the BLMs authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. The use of automation equipment that will monitor and alarm is required when a well's packer, tubing, or casing competence is questionable.
 - e. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD a plan for correction and the anticipated date of correction. The lack of records documenting a continuous fluid packed casing will require rapid correction. Verbal approval for the plan may be given from a BLM authorized officer, with the NOI filed soon after.
 - f. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.