

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-38374
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Nadel and Gussman HEYCO, LLC		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 1936, Roswell, NM 88202		7. Lease Name or Unit Agreement Name Aid State
4. Well Location Unit Letter B : 330' feet from the North line and 2310' feet from the East line Section 13 Township 17S Range 28E NMPM EDDY County		8. Well Number #9
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3703' GR		9. OGRID Number 258462
		10. Pool name or Wildcat Empire Glorieta-Yeso

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Production Csg and Cmt Reports
☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/6/11- TD 7 7/8" hole @ 5,450' Run 127 jts 5 1/2" 15.5# J-55 casing. Lead: CMT w/ 820 sx Class C wt 11.90 ppc, yield 2.37 cuft/ft, gal/sk 13.52. Tail: 450 sks Starbound "C" wt 13.20 ppg, yield 1.55 cuft/ft, gal/sk 7.86. No problems w/csg or cmt jobs. Plug dn @ 6:17 pm 4/6/11. bump plug @ 1950 psi. Ck float held, did not circ any cmt to pit.

See Attached Dual Laterolog Micro-guard and Spectral Gamma Ray Dual Spaced Neutron Spectral Density log.



3/27/11

Spud Date:

4/7/11

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tammy R. Link TITLE _____ DATE 4/12/11

Type or print name: Tammy R. Link E-mail address: tlink@heycoenergy.com
For State Use Only

PHONE: 575-623-6601

APPROVED BY: Donald Gray TITLE Field Supervisor DATE 4-19-11
Conditions of Approval (if any):

150

SUMMARY CASING AND CEMENTING REPORT

DATE: **4/6/2011**

WELL: **AID ST. #9**
RIG: 1
REP: Keith Cannon

CASING DETAIL

HOLE SIZE: 77/8" DEPTH: 5,450

51/2"		5450.00
51/2" SHOE		<u>0.90</u>
		5449.10
2 JOINTS 51/2" 15.5# J-55 LTC CASING		<u>85.28</u>
		5363.82
51/2" FLOAT COLLAR		<u>0.65</u>
		5363.17
22 JOINTS 51/2' 15.5# J-55 LTC CASING		<u>937.70</u>
		4425.47
1 JOINT 5 1/2" 15.5# J-55 LTC CSG	MARKER JOINT	<u>20.54</u>
		4404.93
12 JOINT 5 1/2" 15.5# J-55 LTC CSG		<u>511.63</u>
		3893.30
1 JOINT 5 1/2" 15.5# J-55 LTC CSG	MARKER JOINT	<u>21.28</u>
		3872.02
91 JOINT 5 1/2" 15.5# J-55 LTC CSG		<u>3878.79</u>
		-6.77
KB TO GL		18.00

REMARKS:

Total Casing Delivered 131 Jts (5,543.14 ') 2 MARKER JOINT (42.29')
ALL CASING WAS DRIFTED, CLEANED, & VISUALLY INSPECTED ON LOCATION.
FLOAT SHOE, FLOAT COLLAR WERE THREAD LOCKED

CENTRALIZERS @ 2x 5406.47, 2x 5363.82, 5277.92, 5150.07, 5022.14, 4894.35, 4766.45, 4638.61
4638.61, 4510.76, 4425.47, 4319.63, 4191.72, 4063.79, 3935.91, 3829.43

EXCESS CASING

CASING NOT USED 2 JTS. NOT USED 17# J-55 LTC (85.27')
DISPOSITION NGP YARD (ARTESIA) 2 JTS 17# J-55

CEMENTING DATA

DISTRICT: Hobbs

1ST STAGE

SUMMARY CASING AND CEMENTING REPORT

Spacer 10 bbls. Fresh

LEAD: 820 Sks. 50/5010 "C"+10%GEL=.3%fl-10+5%SALT+.25%R-38, wt 11.90, yield 2.37, gal/sk
13.52

TAIL: 45 Sks.Starbond"C"+.3%fl-10+.1%c-20+.25%r-38 wt 13.20, yield 1.55, gal/sk 7.86

DISPLACEMENT: 124.8 bbls. Fresh Water, Hit Plug W/ 124 bbls

NOTES: NO PROBLEMS W/ CSG OR CMT JOBS. PLUG DOWN@ 6:17pm 4/6/11. BUMP PLUG @
1950PSI. CK FLOAT HELD, DID NOT CIRC ANY CMT TO PIT.