

OCD-ARTESIA

Form 3160-5
(August 2007)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator
SandRidge E&P, LLC3a. Address
123 Robert S. Kerr Ave.
OKC OK 73102-64063b. Phone No. (include area code)
405-476-60854. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2077 FNL / 1379 FWL
Sec 34, T18S, R30E5. Lease Serial No.
NM033775

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.
NMNM70993X8. Well Name and No.
NBQU #639. API Well No.
30-015-3689910. Field and Pool or Exploratory Area
Benson Queen Grayburg, North11. Country or Parish, State
Eddy County, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Amended csg design
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Attached please find the new casing design for our APD extension request dated 9/16/2010.

Accepted for record

NMOCD DJS

5-3-11

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)
Linda Guthrie

Title Regulatory Manager

Signature

Date 03/02/2011

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

FIELD MANAGER

Date

4/25/11

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

CARLSBAD FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

DRILLING PROGRAM NBQU #63

1. Geological Name of Surface Formation

- a. Permian

2. Estimated Tops of Geological Markers

- a. Top of Anhydrite 330'
- b. Top of Yates 1672' Possibly yield hydrocarbons @ 1650'
- c. Top of Queens 2786' Possibly yield hydrocarbons @ 2800'
- d. Top of Penrose 3003' Possibly yield hydrocarbons @ 3200'
- e. Top of Grayburg 3225'
- f. Total Depth 3500'

No other formations are expected to yield oil, gas or fresh water in measurable volumes. The surface fresh water sands will be protected by setting 11 3/4" casing at 400' and circulating cement back to surface. Potash will be protected by setting 8 5/8" casing at 2500' and circulating cement to surface. Fresh water sands will be protected by setting 5 1/2" casing at 3500' and circulating cement to surface.

3. Casing Program:

<u>Hole Size</u>	<u>Depth</u>	<u>OD Csg</u>	<u>Weight</u>	<u>Collar</u>	<u>Grade</u>	<u>New/Used</u>
14 3/4	400'	11 3/4	47#	ST&C	J-55	New
10 5/8	2500'	8 5/8	32#	LT&C	J-55	New
7 7/8	3500'	5 1/2	15.5#	LT&C	J-55	New
Safety factors:		Burst 1.1	Collapse 1.125	Tension 1.8		

4. Cement Program: (Note yields; and dv tool depths if multiple stages)

- a. 11 3/4" Surface Circulate cement to surface with 240 sks Class C cement + 2% CaCl₂ (wt. 14.8 lbs/gal., Yield 1.34 cuft/sk)
- b. 8 5/8" Intermediate Circulate cement to surface with lead cement from 2000' to surface with 360 sks class C + 5% Salt + 0.25 lb/sk LCM (wt. 12.4 lbs/gal, Yield 2.12 cuft/sk)
Tail Cement: 170 sks Class C + 2% CaCl₂ (wt 14.8 lbs/gal, Yield 1.34 cuft/sk) from 2500' to 2000'
- c. 5 1/2" Production Circulate cement to surface with lead cement from 3300' to surface with 350 sks 50:50 POZ class C + 2% Bentonite + 0.5% F.L. + 0.25 lb/sk LCM + 0.4% anti foam (wt. 11.9 lbs/gal, Yield 2.06 cuft/sk)
Tail Cement: 50 sks Class C + 2% CaCl₂ (wt 14.8 lbs/gal, Yield 1.34 cuft/sk) from 3500' to 3300'

The above cement volumes could be revised pending the caliper measurement from open hole logs. The top of cement is designed to reach surface.