

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	<input checked="" type="checkbox"/>	
FILE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
U.S.G.S.		
LAND OFFICE		
OPERATOR	<input checked="" type="checkbox"/>	

5a. Indicate Type of Lease

State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL  GAS WELL  OTHER

RECEIVED

7. Unit Agreement Name

Name of Operator  
Yates Petroleum Corporation ✓

MAY 06 1983

8. Farm or Lease Name

Address of Operator  
207 South 4th St., Artesia, NM 88210

O. C. D.

Sacra SA

Location of Well

UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM

9. Well No.

5

THE East LINE, SECTION 27 TOWNSHIP 6S RANGE 25E N.M.P.M.

10. Field and Pool, or Wildcat

Pecos Slope Abo

15. Elevation (Show whether DF, RT, GR, etc.)  
3776.3' GR

12. County  
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK   
TEMPORARILY ABANDON   
PULL OR ALTER CASING   
OTHER

PLUG AND ABANDON   
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK   
COMMENCE DRILLING OPNS.   
CASING TEST AND CEMENT JOB   
OTHER Intermediate Casing

ALTERING CASING   
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

PD 1492'. Ran 37 joints of 8-5/8" 24# J-55 ST&C casing set 1492'. 1-Type "M" notched guide shoe set 1492'. No insert float. Cemented w/450 sacks BJ Lite, 1/4#/sack celloflakes and 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 1:30 PM 4-30-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 8 hours. Ran Temperature Survey and found top of cement 980'. Ran 1". Tagged cement at 890'. Spotted 150 sacks Surefill, 10#/sack gilsonite, 1/2#/sacks celloflakes and 4% CaCl2. PD 9:15 PM 4-30-83. WOC 1 hours. Ran 1". Tagged cement at 480'. Spotted 50 sacks Class "C" 4% CaCl2. PD 10:15 PM 4-30-83. Cement circulated 10 sacks. WOC. Drilled out 1:30 PM 5-1-82. WOC 24 hours. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 5-6-83

Original Signed By  
Leslie A. Clements

APPROVED BY \_\_\_\_\_

TITLE Supervisor District II

DATE MAY 09 1983

CONDITIONS OF APPROVAL, IF ANY: