

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	✓	
FILE	✓	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	✓	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

OCT 29 1982

O. C. D.
ARTESIA OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6853	
7. Unit Agreement Name	
8. Farm or Lease Name Runyan State	
9. Well No. 2	
10. Field and Pool, or Wildcat Undesignated Penn	
11. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL GAS WELL OTHER

Name of operator
ELK OIL COMPANY ✓

Address of operator
P. O. BOX 310, ROSWELL, NEW MEXICO 88201

Location of Well
UNIT LETTER **C** **990** FEET FROM THE **North** LINE AND **1980** FEET FROM
THE **West** LINE, SECTION **24** TOWNSHIP **9S** RANGE **26E**

15. Elevation (Show whether DF, RT, CR, etc.)
3797

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:


SUBSEQUENT REPORT OF:


PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well on 10/22/82. Drilled 12 1/4" hole to 958'. Ran 958' 8 5/8" 24# casing. Cemented w/800 sx Halliburton Lite (600 sx lite + 200 sx neat) containing 5# gilsonite, 1/4# flocele, 9# salt, 2% calcium chloride/sx, circulate 100 sx. WOC 18 hours; test to 1000#, test OK. Resume drilling.

17. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  TITLE President DATE 10/27/82

APPROVED BY  TITLE OIL AND GAS INSPECTOR DATE NOV 3 1982

CONDITIONS OF APPROVAL, IF ANY: