

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

JUL 21 1988

O. C. D.
ARTESIA OFFICE

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG 939

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation	7. Unit Agreement Name
3. Address of Operator 105 South 4th St., Artesia, NM 88210	8. Farm or Lease Name Witz VN State
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 9S RANGE 26E NMPM.	9. Well No. 3
15. Elevation (Show whether DF, RT, GR, etc.) 3806.5' GR	10. Field and Pool, or Wildcat Wildcat Penn
	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Squeeze perms, reperforate <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-16-88. Set cement retainer at 6135'. Squeeze perforations 6164-6364' w/50 sx cement to 1500 psi. Reverse out 10 sacks cement. WIH and perforated 10 .42" holes at 6054' 56, 58, 69, 73, 76, 86, 89, 93, and 6097'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Williams TITLE Production Supervisor DATE 7-20-88

APPROVED BY Mike Williams TITLE _____ DATE JUL 22 1988

CONDITIONS OF APPROVAL, IF ANY: