

elist
up

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV - 9 1993

WELL API NO. 30-005-62987
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Sacra SA Com
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 11
3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471	9. Pool name or Wildcat Pecos Slope Abo
4. Well Location Unit Letter G : 2310 Feet From The North Line and 2310 Feet From The East Line Section 35 Township 6S Range 25E NMPM Chaves County	

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3716' GR
--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 11:30 AM 10-28-93. Set 40' of 20" conductor pipe and redi-mix to surface. Resumed drilling 17-1/2" hole 5:15 PM 11-1-93. Ran 13-3/8" 54.5# J-55 ST&C casing set 805'. Guide shoe set 805', insert float set 762'. Cemented with 450 sx PSL "C" with 1/2# Celloseal + 3% CaCl2 (yield 1.84, wt 12.7). Tailed in with 250 sx "C" with 2% CaCl2 (yield 1.32, wt 14.8). PD 11:15 PM 11-3-93. Bumped plug to 600 psi, float held okay. Circulated 100 sacks cement. WOC. Drilled out 5:45 PM 11-4-93. WOC 18 hours and 30 minutes. Reduced hole and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 11-8-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II TITLE _____ DATE _____

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: --

NOV 12 1993