

NO. OF COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

MAR 25 1974

30-011-20014

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE <input checked="" type="checkbox"/>	FEE <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-7064	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Wildcat		8. Farm or Lease Name Good- State	
2. Name of Operator J. D. Sandefor, 111		9. Well No. 1	
3. Address of Operator 310 North Willis St. Abilene, Texas 79603		10. Field and Pool, or Wildcat Wildcat	
4. Location of Well UNIT LETTER 1 LOCATED 664 FEET FROM THE North LINE AND 663 FEET FROM THE East LINE OF SEC. 21 TWP 1-N RGE 27-S NMPM		12. County DeBaca	
19. Proposed Depth 7000		19A. Formation Basement	
20. Rotary or C.T. Rotary		21. Elevations (Show whether DF, RT, etc.) 1479.75 GL	
21A. Kind & Status Plug. Bond \$10,000 Blanket		21B. Drilling Contractor Cactus	
22. Approx. Date Work will start 30 May 1974			

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
16 1/4	13 3/8	54	300	350	Circulate
11	8 5/8	24	1500	450	Circulate
7 7/8	5 1/2	15.5	6500	350	4400

Blowout Preventer:

Cameron 3000, Hydraulic operated with remote controls.
Master gate and pipe rams. Pressure test to 1000

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,

EXPIRES 6-28-74

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed [Signature] Title Engineer Date 10 March 1974

(This space for State Use)

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE MAR 28 1974

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 13 3/8" 85/8" casing