OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Oil Cous. Comm.

Name BIL AND GAS INSPECTOR

Title

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworm to before a natural triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be

Indicate nature of	nal instructions in the Rules a report by checking below.	•	
REPORT ON BEGINNING DRILLING OPERA-	REPORT ON REPAI	RING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL	REPORT ON PULLI ALTERING C	NG OR OTHERWISE ASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEP	ENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			
June 14	, 1950 Az	tesia, New Mexi	.00
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO Fentlemen: Following is a report on the work done and the results of the res		Place B-5307, Assignmented above at the	
Company or Operator	Lyns	202	
Anderson Field,	T. R	, N. 1	
The dates of this work were as follows:	June 8th to 13th	, 1950	`
			19
DETAILED ACCOUNT OF WO DETAILED ACCOUNT OF WO Placed cement plug of 8 sx at 25 another cement plug of 8 sx and cement plug of 6 sx and mudded hearker in cement. Recovered appears of 10 casing. All work don	ained. (Cross out incorrect v RK DONE AND RESULTS (500° and mudded ho mudded hole to 55 nole to surface. croximately 1900°	DETAINED Le to 1400; pl 10; placed anot Set regulation 7* casing, and	aced her
DETAILED ACCOUNT OF WOO Placed cement plug of 8 sx at 25 another cement plug of 8 sx and cement plug of 5 sx and mudded h marker in cement. Recovered app 40° of 10° casing. All work dor Witnessed by Harold Kersey Rame	ained. (Cross out incorrect v RK DONE AND RESULTS (500° and mudded ho mudded hole to 55 nole to surface. croximately 1900°	DETAINED Le to 1400; pl 10; placed anot Set regulation 7* casing, and	abou
Placed cement plug of 8 sx at 25 another cement plug of 8 sx and cement plug of 6 sx and mudded hearker in cement. Recovered app 40 of 10 casing. All work dor	RK DONE AND RESULTS (500' and mudded ho mudded hole to 55 hole to surface. croximately 1900' he by Kersey & Company Company I hereby swear or affirm is true and dorrect. Name	DBTAINED The to 1400; placed anot Set regulation The casing, and spany. Partne	aced her abou
Placed cement plug of 8 sx at 25 another cement plug of 8 sx and cement plug of 8 sx and cement plug of 5 sx and mudded 1 marker in cement. Recovered app 40° of 10° casing. All work dor Witnessed by Name Subscribed and sworn before me this June 50°	RK DONE AND RESULTS (SOO' and mudded he mudded hele to 55 hele to surface. croximately 1900' he by Kersey & Company Company I hereby swear or affirm is true and correct. Name Position Representing Carl	Partner, Truste	abou
Placed cement plug of 8 sx at 25 another cement plug of 8 sx and cement plug of 8 sx and cement plug of 5 sx and mudded 1 marker in cement. Recovered app 40° of 10° casing. All work dor Witnessed by Name Subscribed and sworn before me this June 19 Alexan Carlsey	RK DONE AND RESULTS (SOO' and mudded he mudded hele to 55 hele to surface. croximately 1900' he by Kersey & Company Company I hereby swear or affirm is true and correct. Name Position Representing Carl Compa	DBTAINED The to 1400; placed anote of regulation of the casing, and spany. Partner of the that the information gives the casing of the casin	abor abor

UCT 24 1950