

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico


AREA 640 ACRES  
LOCATE WELL CORRECTLY

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Field Office, Box 725, Artesia, N. Mex.

Home Office, Box 689, Tyler, Texas

Allen, Fair &amp; Pope

Company or Operator

Address

State

Lease

Well No.

2A

in

SW SW

of Sec.

36

T.

17

R. 29

N. M. P. M.

Loco Hills

Field,

Eddy

County.

Well is 990 feet south of the North line and 330 feet west of the East line of section 36

If State land the oil and gas lease is No. B-2023

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is R. W. Fair &amp; G. V. Allen

Address Box 689, Tyler, Texas

Drilling commenced May 1st

19 39

Drilling was completed

June 8th

19 39

Name of drilling contractor C. C. Dodson

Address Artesia Hotel, Artesia, N. Mex

Elevation above sea level at top of casing 3549 feet.

The information given is to be kept confidential until

19

## OIL SANDS OR ZONES

No. 1, from 2650 to 2651 Show No. 4, from to

No. 2, from 2672 to 2686 No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/4"	28#	8	Nat'l	494	Hallib.				
7" O.D.	22#	10	Y'twn	2556	Hallib.				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/4"	494	50	Halliburton	Heavy	3 Tons
8 1/4"	7" O.D.	2556	100	Halliburton	Heavy	5 Tons

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
5"	Tin	Nitro	70 Qts	6-12-39	26 7102686	2636

Results of shooting or chemical treatment Increased Production—Well flowed 20 bbls hr through tubing

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing June 12th, 19 39

The production of the first 24 hours was 480 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

J. D. Combs, Driller V. A. Lane, Driller

G. C. Hill, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22nd

Artesia, N. Mex June 22, 1939

Place

Date

day of June, 19 39

Name C. M. Pope, Jr.

SEAL

Position Secretary

Barbara A. Wood

Notary Public

Representing Allen, Fair &amp; Pope

Company or Operator

My Commission expires May 31st, 1941

Address Box 725, Artesia, New Mexico

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	25		Caliche
25	80		Clay and sand
80	105		Red rock
105	185		Sand
185	225		Red Gumbo
225	275		Anhy and shale
275	330		Gyp
330	400		Anhy
400	405		Red shale
405	480		Anhy and red bed
480	485		Potash
485	492		Anhy
492	785		Salt
785	800		Red shale and salt
800	835		Anhy
835	840		Shale
840	985		Salt
985	2160		Anhy, red shale, lime.
2160	2188		Red sand
2188	2275		Lime
2275	2320		Anhy
2320	2345		Lime
2345	2405		Sandy shale, anhy
2405	2420		Lime
2420	2445		Anhy
2445	2450		Red shale
2450	2460		Anhy and grey sand
2460	2470		Red sand
2470	2502		Anhy
2502	2671		Lime
2671	2672		Shale
2672	2686		Oil sand saturated
2686	2699		Lime
2699			Total depth