

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-060529

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Beeson "F" Fed.

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Loco Hills Q-G-SA

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 31, 17-S, 30-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

4001 Penbrook Street, Odessa, TX 79762

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit G, 2310' FNL & 2310' FEL

14. PERMIT NO.

30-015-04412

15. ELEVATIONS (Show whether SF, ST, OR, etc.)

3572' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 11-03-93 - MIRU Contacted BLM 11-01-93. Notified of operations to P&A. Dig out cellar area ND wellhead equip. NU BOPs.
- 11-04-93 - Mix and pump 55 sxs. class C Neat. Spot Plug #1 F/2750' T/2500'. Mix and pump 25 sxs. Class C Neat Spot Plug #2 F/2294' T/2194'. Mix and pump 20 sxs. Class C Neat. Spot Plug #3 F/1205' T/1105'. Mix and pump 45 sxs. Class C Neat. Spot Plug #4 F/464' T/200'. Plug #1
- 11-05-93 - Tag cmt. @154'. Isolate csg. leak. Found leak between 120' & 90'. TOOH LD pkr. TIH O.E. to 154'. Mix and pump 77 sxs. Class C Neat. Load csg. w/cmt. Continue to pump cmt. Lost circulation @ surface. Mix and pump 25 sxs. Class C Neat down braden head & circ. cmt. to surface and fill 7" to surface again. ND BOP

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED

L. M. Sanders
L. M. Sanders

TITLE

Supv. Regulatory Affairs

DATE 11-11-93

(915) 368-1488

(This space for Federal or State office use)

APPROVED BY

(ORIG. SGD.) JOE G. LARA

TITLE

Petroleum Engineer

DATE

12/7/93

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side