

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico


AREA 640 ACRES  
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Aston & Fair

Schouriech Unit

Schouriech

Well No. 7 B

Company or Operator

in

of Sec. 32

T. 17 S

R. 30 E

N. M. P. M. Loce Hills

Field, Rddy

County.

Well is 1650

feet south of the North line and 4950

feet west of the East line of Sec. 32

If State land the oil and gas lease is No. B-4108

Assignment No. 13

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Address

Drilling commenced Sept. 7,

19 51

Drilling was completed Oct. 20

19 51

Name of drilling contractor A. J. Smith

Address Artesia, New Mexico

Elevation above sea level at top of casing 3591

feet.

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

No. 1, from 2850

to 2885

No. 4, from

to

No. 2, from 3078

to 3087

No. 5, from

to

No. 3, from

to

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8-5/8	28#	8	Seamless	475				
5 1/2	14#	10	"	278 1/2				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8-5/8	475'	50	Denton Oil Well Cementing Co.		3 sacks
8"	5 1/2	278 1/2'	100	Denton Oil Well Cementing		100 "

PLUGS AND ADAPTERS

Heaving plug—Material

Length

Depth Set

Adapters—Material

Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
750	Gals.	Hydrefrac		10/19/51	3078-3087	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from

feet to

feet, and from

feet to

feet.

Cable tools were used from 0

feet to 3100

feet, and from

feet to

feet.

PRODUCTION

Put to producing Oct. 20

19 51

The production of the first 24 hours was 150

barrels of fluid of which 100

% was oil;

% emulsion;

% water; and

% sediment. Gravity, Be

If gas well, cu. ft. per 24 hours

Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

E. F. Ballieu

Driller

Walter Cluney

Driller

C. S. Howell

Driller

W. Drumbly

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.