

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TWO COPIES
(Other instructions on reverse side)Form approved
Budget Bureau No. 42-R1424
5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well	2. NAME OF OPERATOR Atlantic Richfield Company	3. ADDRESS OF OPERATOR P.O. Box 1978, Roswell, New Mexico 88201	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL, 660' FEL (Unit Letter P)	5. INDIAN, ALLOTTEE OR TRIBE NAME	6. UNIT AGREEMENT NAME	7. FARM OR LEASE NAME Turner "A"	8. WELL NO. 11	9. FIELD AND POOL, OR WILDCAT Grayburg-Jackson	10. SEC. T. R. M. OR BLK. AND SURVEY OR AREA Sec 18, T12S, R31E	11. COUNTY OR PARISH Eddy	12. STATE N.M.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, ST, GR, etc.) 3695' Grd.										

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREAT	☐	FRACURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☒
REPAIR WELL	☐	(Other) Run 4 1/2" Innerstring	☒
(Other)	☐	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MI & RU plg unit 12/27/69. Cleaned out 3433-3451 (TD). Ran 1 1/2" OD 9.5# 8R Midco-50 csg w/guide shoe & float collar equal to and set @ 3452.26', bottomed @ 3451'. Cemented w/200 sx Class "C" cement w/5# salt/sk, 5# gilsonite/sk, 1% CaCl & 1/4# Flocele/sk. Job complete @ 3:00 PM 12/29/69. WOC. Top of cement @ 800' by temperature survey. WOC to 7:00 AM 12/31/69. Drld float collar & cement 3418-3441' (PBD). Perforated Jackson formation @ 3330, 3331, 3342, 3348, 3359, 3363, 3367, 3375, 3380, 3391, 3399, 3403, 3417, 3425, 3426, 3431, 3437 w/one 0.42" JS (17 holes). Treated perfs 3330-3437 w/3000 gallons 15% LSTNE HCl acid & ball sealers. Ran 2-3/8" tbg w/Johnston 101-S tension pkrr set @ 3275'. Work complete @ 4:00 PM 1/3/70

RECEIVED
JAN 9 - 1970

18. I hereby certify that the foregoing is true and correct

SIGNED

D. D. Bridges

TITLE

Dist. Drlg. Supervisor

DATE

1/3/70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD PURPOSES

JAN - 9 1970

ACTING

District Engineer

*See Instructions on Reverse Side