clsí

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210 5 L

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1993

	Expires	M	ncp	31,	199	3
ease	Designal	non	and	Ser	لعا	No

SUNDRY NOTICES AND REPORTS ON WELLS Description of the company of the proposals to drill or to deepen or reducty to a different reservoir.

	<u> </u>	<u> </u>	<u>-A</u>	
lf	induan.	Allottee	or Tribe	Name

OSC ALLEGATION CONTRACTOR		! N/A	
SUBMIT IN TRIP	PLICATE	7. If Unit or CA. Agreement Designation	
1. Type of Well		N/A	
Oil Gas Other	_	8. Well Name and No.	
2. Name of Operator /		Turner "A" #33	
Socorro Petroleum Company	· • • • • • • • • • • • • • • • • • • •	9. API Well No.	
3. Address and Telephone No.	RECEIVED	30-015-05231	
20 N. Broadway, Suite 1500, Oklahoma City,	, OK 73102 (405)552-4560	10. Field and Pool, or Exploratory Area	
Location of Well (Footage, Sec., T., R., M., or Survey Description)		Fren Seven Rivers	
1650' FSL & 2058' FWL	J UL 15. 94	11. County or Parish, State	
Sec. 18-T17S-R31E	O. C. D.	Eddy County, New Mexico	
2. CHECK APPROPRIATE BOX(s) TO IN	DICATE NATURE OF WOTICE, HEP	ORT, OR OTHER DATA	
TVOC OF CURMICCION	TYPE OF ACTIO	M	

TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Issent	Abandonment	Change of Plans
_	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
_	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
- I	X Other Temporarily Abandon	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertanent detail, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plans are to temporarily abandon this wellbore by first plugging back with sand to 1880' (approximately 50' above the top of the 5 1/2" liner) and then spotting 30 sacks of Class "C" cement containing 2% CaCl in the 7" production casing @ 1870'. The top of the cement plug should be at $1710' \pm$. After allowing the cement to set for 24 hours, the cement plug and 7" production casing will be tested to 500 psi. This test will be witnessed by a BLM representative.

In lieu of plugging this well, it is requested that it be granted a temporarily abandon status following the above described work including the passing of a 500 PSIG Mechanical Integrity Test. This wellbore is located within an active Grayburg-Jackson waterflood project and is a deepening candidate during the infill development program now being evaluated and implemented. The well's current completion interval, the Seven Rivers, also appears to have secondary recovery potential. Plugging this well would necessitate it being redrilled at a future date.

14. I hereby certify that the foregoing is true and correct Signed Davidy Doctor	Tide Randy Jackson, District Engineer	Date 6/14/94
(Thus space for Federal or State office use) Approved by (ORIG. SGD.) JOE G. LARA Conditions of approval, if any: Sec attached	Title PETROLEUM ENGINEER Test to be performed	Dom 7/13/94 within 90 days.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Rev. 5/23/94)

BUREAU OF LAND MANAGEMENT CARLSBAD RESOURCE AREA

Temporary Abandonment of Wells on Federal Lands

. 4

Conditions of Approval

According to 43 CFR 3162.3-4-c, " No well may be temporarily abandoned for more than 30 days without the prior approval of the authorized officer".

Temporary Abandonment (TA) status approval requires a successful casing integrity test as follows:

- 1. Contact the appropriate BLM office at least 24 hours prior to the scheduled Casing Integrity Test. For wells in Eddy County call (505) 887-6544; for wells in Lea County call (505) 393-3612.
- A bridge plug or packer shall be set at a maximum of 50 feet above any open perforations or open hole.
- 3. All downhole production/injection equipment (tubing, rods, etc.) shall be removed from the casing if they are not isolated by a packer.
- 4. The production casing shall be filled with corrosion inhibited fluid and pressure tested to 500 psi. The casing shall be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off.

Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment (TA) status for 12 months provided that the operator:

- 1. Submits a subsequent Sundry Notice requesting TA approval,
- 2. Attaches a clear copy or the original of the pressure test chart,
- 3. And attaches a detailed justification why the well should not be plugged and abandoned.

The TA status could be extended without another casing integrity test provided there was no leak-off during the test.

If the well does not pass the casing integrity test, then the operator shall within 30 days submit to BLM for approval one of the following:

- 1. A procedure to repair the casing so that a TA approval can be granted.
- 2. A procedure to plug and abandon the well.