

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN "PLICATE"
(Other instrs on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐ Water Injection Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR Atlantic Richfield Company		7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR P.O. Box 1978, Roswell, New Mexico 88201		8. FARM OR LEASE NAME Turner "A"	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FNL, 1980' FEL (Unit Letter B)		9. WELL NO. 19	
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT Grayburg-Jackson	
15. ELEVATIONS (Show whether DV, RT, GR, etc.) 3660' Grd		11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA Sec. 19, T17S, R31E	
		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Run 4 1/2" Innerstring ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

MI & RU PU 12/31/69. Cleaned out to 3423' TD. Ran 111 lbs 4 1/2" OD 8R 9.5# Midco-50 ST&C casing w/guide shoe & float collar equal to & set @ 3421.92" GL. Cemented w/200 sx Class "C" cement containing 5# salt/sk, 5# gilsonite/sk & 1% CaCl. Plug down @ 12:00 noon 1/3/70. Top of cement @ 1220' by temperature survey. WOC to 7:00 AM 1/5/70. Drld out rubber plug, float collar & cement 3389-3418' SLM. Tested 4 1/2" casing to 1500# for 30 min. Held OK. Perforated w/one 1/2" JS ea @ 3348, 3352, 3349, 3363, 3368, 3370, 3374, 3381, 3384, 3392, 3395, 3398, 3401, 3412 & 3415 (15 holes). Set Johnston 101-S PC pkr w/15000# tension on 2-3/8" tubing. Treated perfs 3348-3415 w/2500 gallons 15% LSTNE HCl acid & ball sealers. Job complete @ 10:30 AM 1/6/70. Swabbed back acid water. Returned well to water injection.

18. I hereby certify that the foregoing is true and correct

SIGNED R.D. Bletcher

TITLE Dist. Drlg. Supervisor

DATE 1-17-70

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD PURPOSES
JAN - 9 1970

Date

ACTING District Engineer

*See Instructions on Reverse Side