

From Bill Vaughn
July 14, 48 - used in filing

RECEIVED
JUL 14 1948
HOBBS OFFICE

FORM C-105

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Danciger Oil & Refining Company, W. T. Waggoner Building, Fort Worth, Texas

Company or Operator
Mancil E. Turner

Address

Well No. 20-A

in SW/SE/NE

of Sec. 19

T. 17-S

Lease

R. 31-S, N. M. P. M., Grayburg-Jackson Field, Eddy County.

Well is 2310 feet south of the North line and 990 feet west of the East line of Section 19.

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Mancil E. Turner Address Artesia, New Mexico

The Lessee is Danciger Oil & Refining Company Address Fort Worth, Texas

Drilling commenced April 15 1948 Drilling was completed June 6 1948

Name of drilling contractor Kersey & Company Address Artesia, New Mexico

Elevation above sea level at top of casing 3698 feet. G.L.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 1875 to 1878 No. 4, from to

No. 2, from 1910 to 1920 No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
7"	20#	8 R	Spang	510'					
5 1/2"	14#	"	"	1866'					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
	7"	510'	80	Halliburton		
	5 1/2"	1866'	100	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	4"	Nitro-glycerine	110 Qts.	6/8/48	1875 - 1920	1935

Results of shooting or chemical treatment. Well producing 10 bbls. per day before shooting; after shooting, produced 15 bbls. per day.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 1935 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing June 8 1948

The production of the first 24 hours was 15 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be 37°

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Kersey & Company, Driller

, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 7th

day of July 1948

GRACE O'CONNOR, Notary Public

In and for Tarrant County, Texas

My Commission expires

Notary Public

June 1, 1949

Fort Worth, Texas - July 7, 1948

Place Date

Name E. Smith

Position Secretary

Representing DANCIGER OIL & REFINING COMPANY

Company or Operator

Address Fort Worth, Texas

