Form 3160-5 (June 1990)

UNITED STATES DEPARTMEN. JF THE INTERIOR BUREAU OF LAND MANAGEMENT

Cons. Division

811 S. 1st Street FORM APPROVED

Artegia, NM 88210826000 Merch 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS 5. Lease Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029395B Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name RECEIVED SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation I. Type of Well Other WIW □ Oil Well 8. Well Name and No. 2. Name of Operator DEVON ENERGY CORPORATION (NEVADA) MAY - 6 1997 Turner "B" #8 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, ORTHHOMA CO. DILLAHOMA 78102 (405) 235-3611 30-015-05280 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 660' FNL & 1980' FEL of Section 20-T17S-R31E Grayburg-Jackson Field 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF ACTION		
Abandonment	Change of Plans	
Recompletion	New Construction	
Plugging Back	Non-Routine Fracturing	
Casing Repair	☐ Water Shut-Off	
Altering Casing	Conversion to Injection	
Other Added perforations & acidized	Dispose Water	
	(Note: Report results of multiple completion on Well	
	Completion or Recompletion Report and Log form.)	
	Abandonment Recompletion Plugging Back Casing Repair Altering Casing	

13. Describe Proposed or Completed Operations (Clearly state all bertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work was done on this well:

12/30/96 to 1/2/97 - Ran bit & scraper to 3450' (TD). Tested casing to 500 psi for 15 min, held OK.

1/3/97 - Acidized Middle Jackson perfs 3318'-3448' w/3000 gals 15% HCl acid.

1/4/97 - Perf'd Grayburg & Lovington 2753' - 3174' w/1 SPF (32 - .38" holes). Acidized Lovington perfs 3012'-3174' w/1300 gals 15% HCl acid. Acidized Grayburg perfs 2753'-2961' w/1900 gals 15% HCl acid.

1/5/97 to 1/6/97 - Ran 4 1/2" Johnson 101S nickel plated pkr, seating nipple & 2 3/8" IPC tbg. Set pkr @ 2684'. Tested to 400 psi for 15 min, held OK.

4/24/97 - Put back on injection.

to any matter within its jurisdiction

14. I hereby certify that the foregoing is true and correct		Karen Byers
Signed Koven Buero	Title	Engineering Technician Date 4/28/97
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title _	ACCEPTED FOR RECORD (ORIG. SGD.) DAVID R. GLASSDate MAY U 5 1997