

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Budget Bureau No. 1004-1
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL
LC 029395 (b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

ARCO Oil and Gas Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1610 Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

1980' FSL & 1980' FWL (Unit K)

RECEIVED BY

AUG 28 1986

O. C. D.

ARTESIA OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "B"

9. WELL NO.

17

10. FIELD AND POOL OR WILDCAT

Fren 7 Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

20-17S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. PERMIT NO
30-015-05289

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to P & A as follows:

Plug	Interval	CMT	Remarks
1.	2046' - 1890'	110 sx	- retainer @ 1890'. 100 sx sqz below retainer pump 10 sx on top (2046' - 1946' OH)
2.	1365' - 1265'	20 sx	spot (B-Salt)
3.	650' - 500'	25 sx	- spot (T-Salt)
4.	80' - 0'	30 sx	- perf @ 80'. cmt inside & outside 5½ csg. (csg shoe, surf plug)

Weld on plate w/valve. Install marker.

18. I hereby certify that the foregoing is true and correct

(915) 688-5672

SIGNED

Ken W. Gosnell

TITLE

Engr. Tech. Spec.

DATE

8-8-86

(This space for Federal or State office use)

APPROVED BY

Orig. Spec. Control

TITLE

DATE

8/26/86

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side