


Approval expires 12-31-60.

Form 9-331a  
(Feb. 1951)

(SUBMIT IN TRIPLICATE)



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las CrucesLease No. 029420 (6)Unit Dow "B"

# SUNDRY NOTICES AND REPORTS ON WELLS

|  |  |
|--|--|
| NOTICE OF INTENTION TO DRILL                   | SUBSEQUENT REPORT OF WATER SHUT-OFF        |
| NOTICE OF INTENTION TO CHANGE PLANS            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     | SUBSEQUENT REPORT OF ALTERING CASING       |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        | SUBSEQUENT REPORT OF ABANDONMENT           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    | SUPPLEMENTARY WELL HISTORY                 |
| NOTICE OF INTENTION TO ABANDON WELL            |  |
| <b>Plug Back &amp; Dual Complete</b>           | <b>XX</b>                                  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hebbs, New Mexico - November 14, 1962Well No. Dow "B"  
21 is located 1980 ft. from N line and 660 ft. from E line of sec. 21NE/4 SE/4 Sec. 21  
( $\frac{1}{4}$  Sec. and Sec. No.)17-S  
(Twp.)31-E  
(Range)N.M.P.M.  
(Meridian)Grayburg Jackson  
(Field)Eddy  
(County or Subdivision)New Mexico  
(State or Territory)The elevation of the derrick floor above sea level is 3822 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Summary Notice Form 9-331a "Notice of Intention to Workover" dated June 1, 1960, filed on this well showed attempts of recompletion in the Glorieta and San Andres Zones. We have made an extensive study of the Glorieta Zone of the well and we have come to the conclusion that the Glorieta Zone would not be a commercial producing zone. We plan to continue our workover on this well in the following manner:

1. Set cast iron bridge plug at approximately 7200' and dump 2 sacks of cement on top of bridge plug.
2. Run free point indicator and cut 5-1/2" OD casing at approximately 5000'.
3. Pull one joint of casing and spot 100' plug of cement at free point.
4. Pull 5-1/2" OD casing.
5. Run Gamma Ray Neutron log.
6. Set 6-5/8" OD bridge plug at approximately 3590' and dump 10 sacks of cement on top of bridge plug. (See Reverse Side)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Skelly Oil CompanyAddress Box 38Hebbs, New Mexico(ORIGINAL)  
(SIGNED) H. E. Aab

By

Title Dist. Supt.