

HISTORY OF OIL OR GAS WELL

FRacture treatment - 3225-3281.
 Fan 2 tubing to 3215, loaded hole with 120 bbls. oil, broke formation down at 3000#. Fractured open-hole 3225-3281. with 10,000 gallons sandoil mixed 1# sand per gallon, by Dowell. Max. pressure 2100#. Max. injection rate 19.4 bbls. per minute. Time of treatment 31 minutes. Shut down pressure 1200#. Left shut in 12 hours and the same dropped to 150#. Opened up on 3/4" choke and well kicked off. After recovering all load oil, placed on 20/64" choke and in 21 hours flowed 257 bbls. new oil.

FRACURE TREATMENT - 3225-3281.
 Part 2 tubing to 3215, loaded hole with 120 bbls. oil, broke formation down at 3000#. Fractured open-hole 3225-3281, with 10,000 gallons sandoil mixed 1# sand per gallon, by Dowell. Max. pressure 2100#. Max. injection rate 19.4 bbls. per minute. Time of treatment 31 minutes. Shut down pressure 1200#. Left shut in 12 hours and the sure dropped to 150#. Opened up on 3/4" choke and well kicked off. After recovering all load oil, placed on 20/64" choke and in 21 hours flowed 257 bbls. new oil.