

Form 8-331a
(Feb. 1961)

U. S. G. O. COPY

Budget Bureau No. 42-R368.4.
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**

Lease No. **029419(a)**

Unit **Lynch "A"**

RECEIVED

APR 26 1961

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIAN OFFICE

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	
Drill out plugs & complete well <input checked="" type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico - April 21, 1961

Lynch "A"
Well No. **5** is located **1980** ft. from **{N}** line and **1980** ft. from **{E}** line of sec. **22**
SW/4 NE/4 Sec. 22 **17-3** **31-8** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Grayburg Jackson **Jddy** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3858** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled with rotary tools to a total depth of 5040' in Feb. 1951. The well was plugged and abandoned on Feb. 18, 1951, as a dry hole with 8-5/8" OD casing set at 603' with 150 sacks. We propose to drill out cement plugs and clean out hole from surface to approx. 4000' in the San Andres Formation with cable tools. We will set 5-1/2" OD casing at approx. 3850' and cement with approx. 350 sacks of cement by pump and plug process. We will treat well with approx. 50,000 gals. lse. oil and 50,000# sand.

RECEIVED

APR 24 1961

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Skelly Oil Company**

Address **Box 38**

Hobbs, New Mexico

By **J. N. Sweeney**
Title **Dist. Supt.**