

Drawer DD

0+6-BLM-Roswell, 1-File, 1-Engr. PWS, 1-Foreman EF, 1-JA, 1-BB, 1-Mr. J.A.-Midland

Form 9-331
Dec. 1973

1-Laura Richardson-Midland

Form Approved.
Budget Bureau No. 42-R1424

RECEIVED BY
MAY 10 1984
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
ARTESIA, NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR
Getty Oil Company3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit Ltr. K, 1980 FSL & 1980 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

LC-029418b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Skelly Unit

8. FARM OR LEASE NAME

9. WELL NO.

72

10. FIELD OR WILDCAT NAME

Grayburg - Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T-17S, R-31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3873' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
DEC 15 9 04 AM '83
BUR. OF LAND RIGHT
ROSWELL DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/1/83 Rig up unit.
12/2/83 Pull pump, rods, and tbq. By CRC, ran temp. survey 500'-3835'.
12/3/83 Ran plug & pkr., set plug @ 2686', test @ 1000# and held (old squeezed perfs 2508-2410). Set pkr above perfs, no leak.
12/5/83 Ran BP, set @ 2300'. By CRC, ran cement bond log 2300'-surface. Top cement @ 2020', free pipe to 1200', bridges 1200-1167', 1005 = 994, 970-974, 912-916, 902-906, 878-880.
12/6/83 TIH w/ pkr, spot 2 sxs. sand on RBP. TOH. Rig up CRC, perf 2 holes (.40") @ 2000'. Ran and set pkr @ 1903'. By Howco pump 50 bbls. fresh and 150 bbls. brine, never broke circ. By Howco, cement w/ 400 sxs. lite and 100 sxs. class "C". Sting out of retainer and circ, 8 sxs. WOC. By CRC, tag TD @ 904', top cmt @ 1840'.
12/7/83 PU 3 7/8" bit, DC's and tbq. Tag retainer @ 1903', had 2' cmt. on top of retainer. Drill retainer and 35' soft cmt. Raise bit to 1900', press. csg to 750#
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Area Superintendent DATE December 13, 1983

Date RECEIVED FOR RECORD

(This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL

TITLE _____ DATE _____

Carlsbad

NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

12/8/83

Finished drilling cmt. and retainer to 2000' and stinger to 2010'. Press. up to 500#, OK. TIH to RBP at 2300', wash sand and TOH. TIH and retrieved RBP. TIH w/ 3 7/8" bit and scraper, tag @ 3630' (PBSD - 3843'). Drill 15' bridge and fell free to 3823'. Cleaned out to 3843'. TOH.

12/9/83

Ran, set and tested tbq. to 5000#, OK. SN @ 3502' Ran 2" x 1 1/2" x 16' pump and rods. Start pumping 10 x 120 SPM.