

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.B.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO RECEIVED

Form C-103
Revised 10-1-78

DEC 16 1981

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	647

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. D.

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Injector	7. Unit Agreement Name Artesia Unit
2. Name of Operator DEPCO, Inc.	8. Farm or Lease Name Artesia Unit
3. Address of Operator 800 Central, Odessa, Texas 79761	9. Well No. 7
4. Location of Well UNIT LETTER D, 480 FEET FROM THE North LINE AND 330 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 17s RANGE 28e NMPM.	10. Field and Pool, or Wildcat Artesia (Q, Gry, SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3672 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DEPCO intends to run a retainer to approximately 2275' and squeeze perfs (2323-28, 2347-50) with approximate 75 sx. cement, then fill hole with mud ladden fluid to approximately 1800'. Perforate squeeze hole at approximately 1775' and run a retainer to approximately 1750' and squeeze with approximately 100 sx. cement. Then fill hole with mud ladden fluid and set a 10 sx. cement plug at the surface with a dry hole marker.

* R.F. c 630' + squeeze w/45 SXS
Fill hole on backside of 8 5/8"

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leon Standard Leon Standard TITLE Field Engineer DATE 12-14-81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE DEC 21 1981

CONDITIONS OF APPROVAL, IF ANY:

* As noted above

Notify N.M.C.C.C. in sufficient time to witness
Plugging