

Copy to S.F.

UNMCCC COPY

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME Skelly Unit	
2. NAME OF OPERATOR Getty Oil Company ✓		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR P.O. Box 730 Hobbs, New Mexico 88240		9. WELL NO. 35	
4. LOCATION OF WELL (Report location clearly and in accordance with any State REGULATIONS ARTESIA, OFFICE See also space 17 below.) At surface 660 FSL & 1980 FEL		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3901 GR	
		12. COUNTY OR PARISH Eddy	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other) Bring cement above 7-Rivers		<input checked="" type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
FRACTURE TREATMENT	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
SHOOTING OR ACIDIZING	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- (1) Pull rods and tubing.
- (2) Run Cement Bond Log.
- (3) Perforate and bring cement above top of 7-Rivers.
- (4) Run Temperature Survey.
- (5) Drill out cement.
- (6) Rerun tubing and rods.
- (7) Place well on production.

RECEIVED
FEB 16 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Steve J. Quachet

TITLE Area Superintendent

DATE 2-14-78

(This space for Federal or State office use)

Joe M. Lora

ACTING DISTRICT ENGINEER

FEB 22 1978