

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

JUL - 9 1992

WELL API NO.

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-10714

7. Lease Name or Unit Agreement Name

G-J West Coop Unit

8. Well No.  
61

9. Pool name or Wildcat  
Grbg Jackson Sr Q Grbg SA

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER TA

2. Name of Operator  
Marbob Energy Corporation

3. Address of Operator  
P.O. Drawer 217, Artesia, N.M. 82810

4. Well Location  
Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 16 Township 17-S Range 29-E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3564.7" GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- (1) Spot 50 sacks cement at 2662', wait on cement, tag at 2275' not enough plug
- (2) Spot 25 sacks cement at 2275', wait on cement, tag plug at 1887'
- (3) Load hole with mud
- (4) Spot 25 sacks cement at 1887'
- (5) Casing parted at 516' Set packer at 300' and squeeze with 90 sacks cement, wait on cement.
- (6) Perforate casing at 300'
- (7) Circulate cement to surface between 4-1/2" and 8-5/8" casing -Set up P.A. marker

Post ID-2  
7-14-92  
P+H

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Raymond M. Mahon*

TITLE

*Superintendent*

DATE

6-10-92

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

*Johnny Robinson*

TITLE

OIL AND GAS INSPECTOR

DATE

10-27-92

CONDITIONS OF APPROVAL, IF ANY:

OK  
LW